



TECHNICAL DATA				
EXTERNAL DIMENSIONS				
width	600 mm			
depth	680 mm			
height	850 mm			
WEIGHT	67.5 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	6650 W			
WATER HARDNESS	2-8 °f			
INLET WATER PRESSURE	200-400 kPa			
CROCKERY DIMENSIONS				
plates diameter	400 mm			
dishes max. height	400 mm/EURO-NORM			
RACK DIMENSION	500X500 mm			
RACK EQUIPMENT	1XC86/A - 1XC44 - 1X575005			
WASHING CYCLES (sec)	1 (60)	2 (90)	3 (120)	4 (180)
WATER SUPPLY 55°C				
racks/h ^(*) (¹)	53	40	30	20
WATER SUPPLY 10°C				
racks/h ^(*) (¹)	25	25	25	20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 l			
BOILER CAPACITY	5.7 l			
BOILER HEATING ELEMENT	6000 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	16.5 l			
TANK HEATING ELEMENT	2700 W			
TANK TEMPERATURE (SET)	55°C			
PUMP POWER	650 W (340 l/min ^{***})			
DRAIN PUMP (optional)	25 W h MAX draining 0.8 m (40 l/min ^{***})			
NOISE	61,3±0.7 dB(A)			

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.