



	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 32 - Ø 40
	DRAINING PIPE ( DRAIN PUMP) Ø 28
	ELECTRICAL SUPPLY

TECHNICAL DATA				
<b>EXTERNAL DIMENSIONS</b>				
width	1490 mm			
depth	885 mm			
height	1970/2295mm (door open)			
WEIGHT(basic version)	340 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	14800 W			
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200-400 kPa			
<b>CROCKERY DIMENSIONS</b>				
size allowed	820 mm			
<b>RACK DIMENSIONS</b>				
1350x725 mm				
<b>RACK EQUIPMENT</b>				
1XC86/A - 1XC97/A - 1X93600				
WASHING CYCLES (min)	1 (3)	2 (6)	3 (9)	4 (12)
<b>WATER SUPPLY 55°C</b>				
racks/h(*) <sup>(1)</sup>	20	10	6	5
<b>WATER SUPPLY 10°C</b>				
racks/h(*) <sup>(1)</sup>	10	10	6	5
WATER CONSUMPTION / CYCLE	8,6 L			
BOILER CAPACITY	20 L			
BOILER HEATING ELEMENT	9000 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	148 L			
TANK HEATING ELEMENT	9000 W			
TANK TEMPERATURE (SET)	55°C			
WASHING PUMP POWER	2900 W (950 L/min <sup>***</sup> ) x 2			
RINSING PUMP POWER	250 W (150 L/min <sup>***</sup> ) x 2			
DRAIN PUMP (optional)	190 W (120 L/min <sup>***</sup> )			
ACOUSTIC PRESSURE	71,9 dB(A)			

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.