



FED-X S/S Three Door Sandwich Counter - XSS7C18S3V

Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Compatible for 8 x 1/3 GN Pan up to 150mm deep
- 1 shelf per door, GN1/1 pan compatible
- Self-closing doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls
- Rapid recovery rate
- Optional 2 and 3 drawer units available in lieu of doors
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1234mm W x 580mm D x 564mm H
- Display top can hold temperature for up to 4 hours from pre-chilled environment

Description

FED-X S/S Three Door Sandwich Counter - XSS7C18S3V

- Net Capacity: 417L
- Cooling System: Fan forced cooling
- Temperature range: +2-+8 ° C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 40%
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Compatible for 8 x 1/3 GN Pan up to 150mm deep
- 1 shelf per door, GN1/1 pan compatible
- Self-closing doors with heavy duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls
- Rapid recovery rate
- Optional 2 and 3 drawer units available in lieu of doors
- Ebm-papst evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1234mm W x 580mm D x 564mm H
- Display top can hold temperature for up to 4 hours from pre-chilled environment

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

| | |
|---------------------|---|
| Net Weight (Kg) | 130 |
| Width (mm) | 1795 |
| Depth (mm) | 700 |
| Height (mm) | 1406 |
| Packing Width (mm) | 1830 |
| Packing Depth (mm) | 730 |
| Packing Height (mm) | 1160 |
| Power | 240V; 50V; 10A; 320W |
| Warranty | 2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice |