



FED-X S/S Four Door Upright Fridge - XURC1410S2V

Quick Overview

- Net Capacity: 1300L
- Cooling System: Fan-forced cooling
- Temperature range: -2Â° ~+8Â° C
- Compressor: Embraco/Secop
- Controller: Dixell
- Ambient Temperature: 43Â° C
- RH: 60%
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Ebm-papst evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1364mm W x 702mm D x 1401mm H
- 1/2 split door system can lower yearly running cost by up to 30%

Description

FED-X Stainless Steel Four Door Upright Fridge - XURC1410S2V

Key Features

- Net Capacity: 1300L
- Cooling System: Fan-forced cooling
- Temperature range: -2 ° ~+8 ° C
- Compressor: Embraco/Secop
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 60%
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of 2/1 gastronorm compatible shelves
- Self-closing lockable doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Ebm-papst evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1364mm W x 702mm D x 1401mm H
- 1/2 split door system can lower yearly running cost by up to 30%

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Net Weight (Kg)	188
Width (mm)	1480
Depth (mm)	830
Height (mm)	2000
Packing Width (mm)	1505
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 430W/2.7A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice