



## FED-X S/S Two half Door Upright Freezer - XURF600S1V

### Quick Overview

- Net Capacity: 388L
- Cooling System: Fan-forced cooling
- Temperature range: -18--22Å ° C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43Å ° C
- RH: 60%
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H
- 1/2 split door system can lower yearly running cost by up to 30%

### Description

FED-X S/S Two half Door Upright Freezer - XURF600S1V

### Key Features

- Net Capacity: 388L
- Cooling System: Fan-forced cooling
- Temperature range: -18--22 ° C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43 ° C
- RH: 60%
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy-saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H
- 1/2 split door system can lower yearly running cost by up to 30%

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

## Your Shipping Specifications

---

Net Weight (Kg)	117
Width (mm)	680
Depth (mm)	810+30
Height (mm)	2000
Packing Width (mm)	710
Packing Depth (mm)	855
Packing Height (mm)	2150
Power	240V, 465W/10A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice