



Fagor Kore 700 Series Electric Pasta Cooker with 2 Baskets CP-E7126

Quick Overview

- Surface tops manufactured in 1.5 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishing
- Hidden screws
- 1.5 mm thick AISI-316L stainless steel wells built into the surface top
- Wells that suit different arrangements and measures of baskets
- The well is filled through the inlet solenoid valve with a two-position switch: average and high-speed filling
- Well drainage through a mechanical ball valve which is resistant to high temperatures and has a safety overflow
- Automatic safety system to stop the current if the water runs out
- Controls with a protective support base and system to prevent water infiltration
- Access to components from the front
- Stainless steel feet with adjustable height
- Machines with IPX5 grade water protection
- High-performance stainless-steel burner located outside of the well with a combustion chamber that enables heating of the base and sides of the well (up to the minimum filling level)
- Burner ignition through electronic spark igniter. With an access tube for manual ignition
- Heating controlled through safety valve

Description

Fagor Kore 700 Series Electric Pasta Cooker with 2 Baskets CP-E7126

Key Features

- Surface tops manufactured in 1.5 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishing
- Hidden screws
- 1.5 mm thick AISI-316L stainless steel wells built into the surface top
- Wells that suit different arrangements and measures of baskets
- The well is filled through the inlet solenoid valve with a two-position switch: average and high-speed filling
- Well drainage through a mechanical ball valve which is resistant to high temperatures and has a safety overflow
- Automatic safety system to stop the current if the water runs out
- Controls with a protective support base and system to prevent water infiltration
- Access to components from the front
- Stainless steel feet with adjustable height
- Machines with IPX5 grade water protection
- High-performance stainless-steel burner located outside of the well with a combustion chamber that enables heating of the base and sides of the well (up to the minimum filling level)
- Burner ignition through electronic spark igniter. With an access tube for manual ignition
- Heating controlled through safety valve

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice

Your Shipping Specifications

Net Weight (Kg)	45
Width (mm)	400
Depth (mm)	730
Height (mm)	850
Packing Width (mm)	822
Packing Depth (mm)	440
Packing Height (mm)	1255
Power	415V, 9kW/3-N
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice