



Fagor Kore 900 Electric Pasta and Noodle Cooker CP-E905

Quick Overview

- Surface tops manufactured in 2 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishes; screws hidden from view
- Wells integrated into the surface top, manufactured in 1.5 mm thick AISI-316L stainless steel
- Wells with 1/1 dimensions, capacity 40 liters. Accommodate different configurations of different-sized baskets
- Well filling using entrance electro valve with two-position switch: medium filling speed and high speed
- Draining of well using high temperature resistant mechanical ball valve with safety overflow
- Automatic safety system that breaks the circuit if the water runs out
- Drainer located at the front for the baskets to be rested on
- Controls with a protective base and system against water infiltration
- High-temperature enameled cast iron flue protector
- Access to the components from the front
- Machines with IPX5 grade water protection
- Electric models with AISI-304 stainless steel heating elements situated in the bottom of the well to heat the water directly
- Heating controls by the energy regulator

Description

Fagor Kore 900 Electric Pasta and Noodle Cooker CP-E905

Key Features

- Surface tops manufactured in 2 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishes; screws hidden from view
- Wells integrated into the surface top, manufactured in 1.5 mm thick AISI-316L stainless steel
- Wells with 1/1 dimensions, capacity 40 liters. Accommodate different configurations of different-sized baskets
- Well filling using entrance electro valve with two-position switch: medium filling speed and high speed
- Draining of well using high temperature resistant mechanical ball valve with safety overflow
- Automatic safety system that breaks the circuit if the water runs out
- Drainer located at the front for the baskets to be rested on
- Controls with a protective base and system against water infiltration
- High-temperature enameled cast iron flue protector
- Access to the components from the front
- Machines with IPX5 grade water protection
- Electric models with AISI-304 stainless steel heating elements situated in the bottom of the well to heat the water directly
- Heating controls by the energy regulator

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice

Your Shipping Specifications

Net Weight (Kg)	65
Width (mm)	400
Depth (mm)	930
Height (mm)	850
Packing Width (mm)	1022
Packing Depth (mm)	440
Packing Height (mm)	1255
Power	415V, 12kW/3-N
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice