



Fagor Kore 900 Series Electric Fry Top FT-E905L

Quick Overview

- 2mm thick 304 S/S surface top
- Laser-cut joints, automatic welding and polishes. Screws are hidden from view
- Fry-tops manufactured in 20 mm thick mild steel, high powered and with rapid temperature attainment
- Rapid reaction and recovery times of the fry-top temperature
- The fry-tops are integrated into the funnelled surface top
- The funnelled housing with rounded edges and corners makes them very easy to clean
- Fry-top tilted towards the front to facilitate fat and liquid collection
- Fitted with an opening for the collection of cooking fat and storage tray with a capacity of up to 2L depending on the model
- Option of easily dismountable side and back splash guards.
- High-temperature enamelled cast iron flue protector
- Access to the components from the front
- Machines with IPX5 grade water protection
- Smooth hot-plate
- Electrically heated models use stainless steel shielded heating elements; temperature controlled by a thermostat, between 100 and 300 ° C
- Optional stands available

Description

Fagor Kore 900 Series Electric Fry Top FT-E905L

Key Features

- 2mm thick 304 S/S surface top
- Laser-cut joints, automatic welding and polishes. Screws are hidden from view
- Fry-tops manufactured in 20 mm thick mild steel, high powered and with rapid temperature attainment
- Rapid reaction and recovery times of the fry-top temperature
- The fry-tops are integrated into the funnelled surface top
- The funnelled housing with rounded edges and corners makes them very easy to clean
- Fry-top tilted towards the front to facilitate fat and liquid collection
- Fitted with an opening for the collection of cooking fat and storage tray with a capacity of up to 2L depending on the model
- Option of easily dismountable side and back splash guards.
- High-temperature enamelled cast iron flue protector
- Access to the components from the front
- Machines with IPX5 grade water protection
- Smooth hot-plate
- Electrically heated models use stainless steel shielded heating elements; temperature controlled by a thermostat, between 100 and 300 ° C
- Optional stands available

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice

Your Shipping Specifications

Net Weight (Kg)	75
Width (mm)	400
Depth (mm)	930
Height (mm)	290
Packing Width (mm)	1022
Packing Depth (mm)	440
Packing Height (mm)	535
Power	415V, 7.5kW/3-N
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice