

Model : _____
 Name : _____
 Project Name : _____

 Project Area : _____
 Project Item : _____

Model WGT-400 B DD AU




General characteristics

- Electronic control panel.
- 3 washing cycles of 90"/120"/180"
- Tank capacity: 15 l./Heating power: 2.0 kW.
- Boiler capacity: 4 l./Heating power: 2.8 kW.
- Wash pump power: 0.3 kW.
- Rinsing consumption: 2.2 l/rinse.
- Upper and lower washing and rinsing arms.
- Thermostop function.
- Wash tank and boiler temperature display.
- Independent cycle for cold rinsing. Not compatible with SOFT models.
- Built-in rinse-aid dispenser.
- Anti-backflow valve fitted.
- Safety thermostat in washing tank and boiler.
- Temperature adjustment: wash 60 °C and rinse 85 °C.
- Supply voltage: 230 V 1N 50/60 Hz.
- Accessories supplied: 2 baskets of 400 x 400 mm, 1 dish bracket and 1 basket for cutlery CU-GW.

Model: WGT-400 B DD AU

Reference	
Baskets/ hour	40
Door clearance (mm)	270
Dimensions (mm)	470 x 530 x 725
Detergent dispenser	Yes
Drain pump	Yes
Water softener	No
Power (kW)	3.05
Voltage (V)	230V-1N-50/60Hz



Packaging dimensions:
Height: 870 MM
Depth: 570 MM
Width: 720 MM
Gross weight: 48,5 KG

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric frequency:	50/60Hz
Electric power (KW):	3,100
230 V three-phase wiring:	3X1,5MM2
Voltage:	220-240V
Amperage (A):	13,3A
Phases:	1N
Engine power (KW):	0,260
Heating power (KW):	2,800
IPX:	IPX3
Noise level (dB):	65

DISHWASHING (Estandarization)

Tipo de calentamiento:	Electric
Electric frequency:	50/60Hz
Drain pump:	Yes
Break tank:	No
Water softened:	No
Double wall:	No
Detergent dispenser:	Yes
Range:	Tech
Market:	Rest
Basket size:	400x400
Voltage:	220-240V
Phases:	1N
Generation:	GRAND
Other configurations:	Non valuated
Extra features:	No

MEASURES AND WEIGHT

Net High (mm):	725
Net Depth (mm):	470
Net Width (mm):	530
Gross weight / packaged (kg):	48,5
Gross height / packaged (mm):	870
Gross width / packaged (mm):	570
Gross length / packaged (mm):	720

