



## Gasmax 4 Burner With Oven Flame Failure GBS4TS

### Quick Overview

- Stainless steel front, galvanized sides
- Natural Gas
- Cast iron open burner
- Thermostat (100° C- 300° C) controlled oven
- Welded frame structure for best stability
- Flame failure control valve
- Adjustable heavy-duty legs
- 12" x12"(30x30cm) cast iron grate
- Anti-clogging pilot cover under the grate
- A pull-out crumb tray with an angled handle in the front
- U shape oven burner
- Thermal coupling safety valve for the oven
- Stainless steel oven door with good insulation
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy access for servicing
- 3/4" rear gas connection
- Continuous pilot
- Each burner power is 38MJ, powerful for peak productivity
- Burner holes are less likely blocked by food waste
- Burner can be easily dismantled for best cleaning
- 0.35mm thick thermocouple can resist 1400° C; heat

### Description

Gasmax 4 Burner With Oven Flame Failure GBS4TS

### Key Features

- Stainless steel front, galvanized sides
- Natural Gas
- Cast iron open burner
- Thermostat (100 ° C- 300 ° C) controlled oven
- Welded frame structure for best stability
- Flame failure control valve
- Adjustable heavy-duty legs
- 12" x12"(30x30cm) cast iron grate
- Anti-clogging pilot cover under the grate

- A pull-out crumb tray with an angled handle in the front
- U shape oven burner
- Thermal coupling safety valve for the oven
- Stainless steel oven door with good insulation
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy access for servicing
- 3/4" rear gas connection
- Continuous pilot
- Each burner power is 38MJ, powerful for peak productivity
- Burner holes are less likely blocked by food waste
- Burner can be easily dismantled for best cleaning
- 0.35mm thick thermocouple can resist 1400 °C heat

2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice

## Your Shipping Specifications

---

Net Weight (Kg)	132
Width (mm)	609
Depth (mm)	855
Height (mm)	1128
Packing Width (mm)	730
Packing Depth (mm)	1030
Packing Height (mm)	890
Power	182MJ/h
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice