



Gasmax 6 Burner With Oven Flame Failure GBS6TSLPG

Quick Overview

- Heavy-duty burners With Flame Failure
- Stainless steel construction
- LPG
- Cast iron open burners
- Thermostat (100 - 300) controlled oven
- Welded frame structure for best stability
- Flame failure control valve
- Adjustable heavy-duty legs
- 12" x12"(30x30cm) cast iron grate
- Anti-clogging pilot cover under the grate
- A pull-out crumb tray with an angled handle in the front
- U shape oven burner
- Thermal coupling safety valve for the oven
- Fully Insulated Stainless steel oven door
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy access for servicing
- 3/4" rear gas connection
- Continuous pilot
- Each burner power is 42MJ, powerful for peak productivity
- Burner holes are less likely blocked by food waste
- Burner can be easily dismantled for best cleaning
- 0.35mm thick thermocouple can resist 1400 heat

Description

Gasmax 6 Burner With Oven Flame Failure GBS6TSLPG

Key Features:

- Heavy-duty burners With Flame Failure
- Stainless steel construction
- LPG
- Cast iron open burners
- Thermostat (100 - 300) controlled oven
- Welded frame structure for best stability
- Flame failure control valve

- Adjustable heavy-duty legs
- 12" x12"(30x30cm) cast iron grate
- Anti-clogging pilot cover under the grate
- A pull-out crumb tray with an angled handle in the front
- U shape oven burner
- Thermal coupling safety valve for the oven
- Fully Insulated Stainless steel oven door
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy access for servicing
- 3/4" rear gas connection
- Continuous pilot
- Each burner power is 42MJ, powerful for peak productivity
- Burner holes are less likely blocked by food waste
- Burner can be easily dismantled for best cleaning
- 0.35mm thick thermocouple can resist 1400 heat

2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice

Your Shipping Specifications

Net Weight (Kg)	167
Width (mm)	914
Depth (mm)	855
Height (mm)	1128
Packing Width (mm)	1040
Packing Depth (mm)	1030
Packing Height (mm)	890
Power	288MJ/h
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice