

INDUSTRY
KITCHENS

www.industrykitchens.com.au 1800 611 058

Hamilton Beach
COMMERCIAL

HBB255-CE Series
HBB255S-CE Series

Rio[®]

1.6 HP Drink Blenders

No More
Ice Chunks



With Wave-Action[®] System

Powerful 1.6 peak HP* motor combined with Wave-Action[®] jar and stainless steel blade crushes ice fast

Lid open and jar pad sensor - prevents blending if jar or lid is not on correctly

Simple high, low, pulse controls for easy operation

Durable and easy-to-use sealed switches ensure long life

Perfect for a variety of cocktail & coffee shop applications

*input power



HBB255-CE Series
(BPA free co-polyester container)

HBB255S-CE Series
(Stainless steel container)



For more Good Thinking[®] visit hamiltonbeachcommercial.com

Hamilton Beach
COMMERCIAL



Lid-Open Sensor
Prevents blending with lid removed



Triple-Seal Lid

Durable Metal Drive Coupling
Delivers ample power and torque to the blade



Optimized Performance
Wide, square jar accommodates larger ingredients, reducing prep time
High-performance stainless steel blade quickly cuts through ice

Ergonomic Handle

**HBB255: 1.4 L (48 oz)
BPA Free, Co-Polyester Container**

**HBB255S: .95 L (32 oz)
Stainless Steel Container**

Protective Brow
Directs drips away from controls

Sealed Switches
For durability and ease of use

Lid Open and Jar Pad Sensor
Prevents blending if jar or lid is not on correctly

1.6 Peak HP* Motor

Powers through fresh and frozen ingredients to create smooth drinks



Wave~Action® System

Continually forces mixture down into the blades for ultra-smooth results

Sure Grip™ Feet
Prevent skidding

HBB255-CE SERIES / HBB255S-CE SERIES BLENDERS

HBB255-CE/-UK



SPECIFICATIONS:

Standard: unit comes with 1.6 HP base, BPA free co-polyster container
Controls: Sealed paddle switches
Weight: 4.5 kg (shipping)
Warranty: 2 years parts & labor
220-240 V 50-60 Hz 3.2 A Class 1



Standard: unit comes with 1.6 HP base, stainless steel container
Controls: Sealed paddle switches
Weight: 4.7 kg (shipping)
Warranty: 2 years parts & labor
220-240 V 50-60 Hz 3.2 A Class 1



HBB255S-CE/-UK

