

Technical information

Polar 2-85



Characteristics

- Supplied with two sealing bars as standard (front/rear)
- Double seal as standard (two sealing wires).
Optional at no extra cost: Cut-off seal/Wide seal (10 mm)
- Easy-to-remove silicone holders for easy cleaning
- Digital time control with ten-program memory as standard
- Soft Air as standard to protect the product and vacuum bag
- Stainless steel casing and flat working plate
- Supplied with eight insert plates for a faster cycle and good product positioning
- IP-65 classification

Opties

- 1-2 Cut-off seal/Bi-Active seal
- Sensor control
- Advanced Control System (ACS)
- Liquid control
- High lid 300 mm
- Gas flush (incl. compressed air connection)
- Connection for external pump
- Extra sealing capacity
- (Lightweight) bag clamp
- Automatic lid (automatic or with foot pedal)

Accessories

- Thermal label printer (only in combination with ACS)
- Inclined insert plate (for liquids and powders)
- Maintenance set for standard maintenance



Specs	Polar 2-85	
Chamber LxWxH (mm)	830x840x255	
Machine LxWxH (mm)	1295x1900x1450	
Voltage	400V-3-50Hz 230V-3-50Hz 220V-3-60Hz 200V-3-50/60Hz	
Pump capacity 50 Hz/60 Hz (m3)	300 / 360	
Machine cycle 50 Hz/60 Hz (sec.)	13 - 26 / 11 - 23	
Power (kW)	5,5 - 6,6	
Weight (kg)	685	
Net seal length (mm) - standard - option	2 x 828 2 x 758	
Sealing bar configuration - standard - option	standaard 	optie

Dimensions mm

