


**PRODUCT ADVANTAGES**

- Minimum space requirement: Vertical or horizontal installation next or on top of a glass-/dishwasher
- Continuous treatment system providing demineralised water for top-quality wash results
- Prevents salt and limescale stains on dishes, glasses and cutlery
- Protects machine against limescale deposits
- Optimises the effectiveness of detergents
- Minimum operating costs at highest capacity
- Bypass function: washing operation of the dishwasher is always guaranteed
- Easy to operate with integrated display
- Fast and easy removal of the pre-filter

**TECHNICAL DATA**

Power supply	230/50/1
Weight (gross / net)	20 kg
Maximum hardness	35 °dH*
Max. conductivity supply water	1,200 µS/cm
Supply capacity Continuously	2 l/min

**INDUSTRY  
KITCHENS**

[www.industrykitchens.com.au](http://www.industrykitchens.com.au) 1800 611 058

\* The installation must be performed according to ATS 5200.101. A back flow prevention for the raw water supply must be installed. A back flow prevention for the drain connection is part of the optional installation kit. From 10° dH ,we recommend installing an upstream water softening system to prevent the blockage of the membrane. Hard water reduces the permeate output and shortens the life of the membrane.

**CONNECTIONS**

Power Cord 230 V	2,000 mm
Raw water connection	R 3/4"
Concentrate drain hose	1,800 mm   ID21/OD28
Pure water hose	2,000 mm   R 3/4"
Flow pressure	1- 6 bar
Max. supply water temperature	35 °C

**DIMENSIONAL DRAWING**
