



PRODUCT ADVANTAGES

- **Compact glasswasher:**
installation height of only 705 mm
or with integrated reverse
osmosis 820 mm
- **VISIOTRONIC-TOUCH control:**
colour touchscreen (displays
text and graphic) in conjunction
with single-button control and
remaining cycle time indication
- **SmartConnect app:** controlling
your warewash operation with
smart technology: status and
messages, usage and operating
costs, hygiene and service
- **CLIP-IN wash and rinse system:**
easy removal without any tools
- **Intelligent data documentation:**
automatic recording of important
operational data and
consumptions and indication on
the display
- **USB-interface:** comfortable
download of operational data in
form of a protocol via USB
- **GENIUS-X² fine filter system:**
advanced filter system with pre-
wash function reduces detergent
consumption up to 35 %
- **Intensive programme:** intensive
rinse cycle to wash glasses with
critical design with raised fresh-
water amount
- **Interlocked strainer:** prevents
operation without tank strainer
- **Optional refill signal:** monitors
contents of external as well as
integrated chemical containers
- **Hygiene programme (in
combination with Hygiene-Tab
INTENSIV)** for removal of calcium
carbonate and other deposits from
wash chamber
- **Thermolabel 71 °C:** default
temperatures setting acc. European
DIN can be switched by operator to
a higher thermolabel setting
- **WATERMARK APPROVED**

TECHNICAL DATA

Cycle times*	1. 75sec 2. 120sec.
Water consumption	1.7 l/rack
Tank capacity	8 litres
Tank heating	0.8 kW
Power supply	240 / 50 / 1 (415 / 50 / 3N)
Booster loading	
Standard	2.8 kW
Alternative	4.1 kW
Total loading	
Standard	3.2 kW 15A
Alternative	4.6 kW 15A (3ph)
Wash pump	0.4 kW 160 l/min
Rack size	400 x 400 mm
Loading height	315 mm
Noise level	57 dB (A)
Weight (gross / net)	64 / 58 kg

*Supplied with 150mm adjustable legs

INDUSTRY KITCHENS

www.industrykitchens.com.au 1800 611 058

*Thermostop guarantees required temperatures with cold water and / or 240 V connection, the actual cycle times extend accordingly.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water softener of the product line HYDROLINE PROTECT.