



HOSHIZAKI

KM-60C HC DRAIN PUMP

Crescent 52kg Ice Maker - Self Contained

Model Number
91000916

PRODUCT FEATURES


- Individually shaped crescent ice.
- Protected by HoshiGuard Antimicrobial Agent.
- CycleSaver® technology includes a double-sided evaporator, uniquely crafted in stainless steel, which produces ice on both sides, resulting in more ice in less amount of time.
- EverCheck™ Control Board with audible alarm and diagnostic features, designed to assist service technicians in diagnosing problems.
- Accessible digital operation panel allows for easy identification of operation status and cause of faults.
- Automated cleaning function makes cleaning simple and saves time.
- Durable stainless-steel exterior.
- Easily removable & cleanable air filters on front panel.
- Accessories: Manual, Scoop, check valve, Hex Bolt legs and 150mm adjustable legs included (water filter and optional hex bolt legs sold separately)

**INDUSTRY
KITCHENS**

www.industrykitchens.com.au 1800 611 058




TECHNICAL DRAWING



PRODUCT SPECIFICATION

Production Capacity / 24hrs	Approx. 52kg @ 21°C Air temp; 15°C Water Approx. 37kg @ 32°C Air temp; 21°C Water
Max Storage Capacity	Approx. 23kg
Freeze Cycle Time	Approx. 26 Min (At. 21°C Air ; 15°C Water)
Ice Production / cycle	Approx. 0.96kg/110pcs
Dimensions	605mm (W) x 610mm (D) x 842mm (H) including hex bolt legs 988mm (H) with 150mm adjustable legs
Cooling	Air
Weight Net/Gross (kg)	45/57
Refrigeration System	Forced Air Circulation
AC Supply Voltage	1 PHASE 220-240V 50Hz / 10amp Plug
Amperage	Running: 1.6A Starting: 8.5A
Refrigerant Charge	R290/90g
Operating Conditions:	
Ambient Temp	7-38°C
Water Supply Temp	7-32°C
Water Supply Pressure	0.07-0.8MPa (0.7-8bar)
Voltage Range	±6%
Electrical consumption	Rated Motor: 255W (Power Factor: 63%)
Water Consumption / 24hrs	Approx. 0.14m³/d(AT. 21°C ; WT 15°C)

DRAIN PUMP



*As height increases, the discharge distance decreases in a directly proportional manner.

- Pump out Drain - Maximum height (H) 1.5metres at length (L) 5metres, Maximum height (H) .5metres at length (L) 15metres.
- Reduced installation time: Internal drain pump simplifies installation task.
- Plug and play efficiency: Easy drain connection without complications.



INSTALLATION REQUIREMENTS

- Ensure the condenser is cleaned periodically as per the manufacturer's manual.
- Do not plug the unit into multi-plug power boards with other appliances
- Installation Consider room ventilation or installing air conditioning to improve environment working conditions.
- Hoshizaki recommends the use of a compatible water filter to prevent non-warrantable scale & sediment complications.

*Refer to manual for full installation & maintenance requirements.

Descriptions and specifications are subject to change at any time, without notice. Illustrations for demonstration purposes. Copyright © 2023 Hoshizaki Lancer Pty Ltd. All right reserved.

For free 6 month extended warranty, register online within 4 weeks of purchase date.
hoshizaki.com.au