

Coolstapler®, cooled by circulating air, for different crockery parts

Make

Manufacturer : HUPFER®
Model : BDC / 54 – 54
No of article: 0161460

Dimensions

Width : 761 mm
Depth: 1092 mm
Height: 900 mm

Execution

Structure

Solid self-supporting structure made from stainless steel.

Characteristics

Basket stacker to store cold foods in portioned cold components on a removable stacking platform, 540 x 540 mm. Constant dispensing height by means of manually adjustable tension spring system, lateral guidance of the platform by means of ball bearing. Hygienically covered by a stainless steel cover hood, double-walled isolation, with profiled handle, cover can be hooked in to the Coolstapler®.

Cooling

Cooling by means of the refrigerant agent R 134a, CFC-free. All-around piping for high cooling capacity and uniform food temperatures. Operation by means of ON/OFF-switch with integrated control lamp, visible at great distance. Inherently stable helix cable with angle plug and suspension for the cable.

Ergonomics

Two ergonomically shaped pushing handles with integrated bumpers protecting against injuries at hands and damages at the appliance. Optimum protection against collision due to the two bumpers.

Chassis

4 swivel castors, 2 of them with brake, castors made from corrosion resistant plastic, free of maintenance, with thread protection, precision ball bearing, Ø 125 mm, according to DIN 18867, part 8.



from the world of Comcater!

National Head Office

156 Swann Drive
Derrimut VIC 3030
Tel: +61 3 8369 4600
Fax: +61 3 8369 4695

Melbourne

96-100 Tope Street
South Melbourne VIC 3205
Tel: +61 3 8369 4600
Fax: +61 3 8699 1299

Sydney

20/4 Avenue of the Americas
Newington, NSW 2127
Tel: +61 2 9748 3000
Fax: +61 2 9648 4762

Brisbane

1/62 Borthwick Avenue
Murarrie QLD 4172
Tel: +61 7 3399 3122
Fax: +61 7 3399 5311

Perth

16/7 Abrams Street
Balcatta, WA 6021
Tel: +61 8 6217 0700
Fax: +61 8 6217 0799

COMCATER
- foodservice equipment

www.comcater.com.au

Technical Data

Connected load :	0,22 kW
Refrigerating capacity:	0,34 kW
Refrigerating agent:	R 134a (CFC-free)
Cooling system:	circulating air
Power supply:	230 V 1N AC 50 Hz
Minimum temp. of crockery: (closed cover)	5 °C
Thermal isolation:	special insulation
Stacking platform:	stainless steel platform 540 mm x 540 mm
Upper dispensing height:	570 mm
Capacity:	up to 244 parts
Enclosure:	IPX 4
CE-mark	approved
Net weight of the appliance:	75 kg
Load capacity:	170 kg

from the world of Comcater!

National Head Office
156 Swann Drive
Derrimut VIC 3030
Tel: +61 3 8369 4600
Fax: +61 3 8369 4695

Melbourne
96-100 Tope Street
South Melbourne VIC 3205
Tel: +61 3 8369 4600
Fax: +61 3 8699 1299

Sydney
20/4 Avenue of the Americas
Newington, NSW 2127
Tel: +61 2 9748 3000
Fax: +61 2 9648 4762

Brisbane
1/62 Borthwick Avenue
Murarrie QLD 4172
Tel: +61 7 3399 3122
Fax: +61 7 3399 5311

Perth
16/7 Abrams Street
Balcatta, WA 6021
Tel: +61 8 6217 0700
Fax: +61 8 6217 0799



www.comcater.com.au