

Heavy-Duty Dismountable Mobile Shelving Unit

RTWZ-16-14-6

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Maximum dimension:	1,400 × 600 mm shelf dimensions
Adjustment dimension:	150 mm
Payload:	200 kg/441 lbs
Castors:	4 swivel castors, 2 with lock, ø 125
Main construction:	Open
Design:	For self-assembly
Weight:	19.71 kg
Width:	1470 mm
Depth:	670 mm
Height:	1652 mm

Adjustable shelf height, made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTWZ-16-14-6 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

All information / dimensions are approximate, technical changes reserved. © Hupfer



National Head Office
156 Swann Drive
Derrimut VIC 3026
Tel: +61 3 8369 4600
Fax: +61 3 8369 4699

www.comcater.com.au

Melbourne
96-100 Tope Street
South Melbourne VIC 3205
Tel: +61 3 8699 1200
Fax: +61 3 8699 1299

Sydney
20/4 Avenue of the Americas
Newington, NSW 2127
Tel: +61 2 8775 9500
Fax: +61 2 9648 4762

Brisbane
46-60 Dunhill Crescent,
Morningside, QLD 4170
Tel: +61 7 3399 3122

Perth
Unit 16, 7 Abrams Street
Balcatta, WA 6021
Tel: +61 8 6217 0700
Fax: +61 8 6217 0799