

Gastronorm trolley for nesting 18×GN 1/1

Product code	Type
0163317	RWG/E 1/18 GN 75-L-U

FUNCTIONAL DESCRIPTION

The Gastronorm trolley for nesting 18×GN 1/1 by Hupfer serves to store food components in GN containers and to transport.

- Hygienic stainless steel surfaces ensure a low-germ environment and quick, residue-free cleaning for strict hygiene compliance
- Can be nested to save space, optimising storage and providing more freedom of movement in busy kitchens and storage areas
- Welded U-shaped shelf rails with push-through and tilt protection secure GN containers and subdivisions safely during transport
- Four smooth-running swivel castors, two with total locks, enable precise manoeuvring and stable positioning in tight spaces
- Polyethylene disc bumpers protect the trolley and surrounding walls from damage, enhancing durability and workplace safety

EQUIPMENT FEATURES

Hygienic stainless steel surfaces
Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

High Manoeuvrability: 4 swivel castors, 2 with total locks
Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

Can be nested to save space
Empty trolleys can be pushed into each other to save space and thus significantly reduce storage requirements. This practical function optimizes the use of space in kitchens and storage rooms and provides more freedom of movement in the work area.

GENERAL TECHNICAL DATA

Nominal format	GN 1/1
Quantity nominal format	18
Width rated	454 mm
Depth rated	619 mm
Nominal height	1.686 mm
Width actual	454 mm
Depth actual	619 mm
Height	1.686 mm
Weight	21 kg
Payload	90 kg
Main material	Stainless steel

Project _____

Order _____

Quantity _____

Date _____



SLIDE-IN PROPERTIES

Insertions construction	U-rails
Number of insertions	18
Insertion size	GN 1/1
Insertion type	Lengthwise insertion
Pitch	75 mm
With tilt protection	Yes
With side push-through protection	Yes

MOBILITY

Set of castors	2 swivel castors with brakes 2 swivel castors
Castor attachment	Round pin
Castor bearing type	Plain bearing
Castor housing material	Plastic
Castor housing colour	Grey
Wheel ø	125 mm
Type of tyre tread	Rubber – Standard
Wheels with thread guard	No
Antistatic wheels	No
Design of the locks	Total lock
Suitable for transport cart washing devices	Not approved
Impact protection construction	Deflector rollers