

Food transport trolley with sliding lid 3×GN 1/1

Product code	Type
0162948-01	SPTW 3EBH 3WF SD

FUNCTIONAL DESCRIPTION

The Food transport trolley with sliding lid 3×GN 1/1 from Hupfer serves storing food components in GN containers, food distribution and keeping food warm in GN containers.

- Robust sliding lid with automatic locking ensures convenient handling and protects against condensation and soiling
- Hygienic stainless steel surfaces provide quick, residue-free cleaning and maintain low-germ conditions
- Thermally separated wells and compartments enable independent transport of hot and cold food while preserving temperatures
- Energy-efficient foil heating reduces heating time and minimises heat loss, saving energy costs
- Ergonomic integrated push handles and corner bumpers offer safe handling and protect equipment from damage

EQUIPMENT FEATURES

Deep-drawn wells

The deep-drawn wells impress with their seamless, joint-free design and meet the highest hygiene standards. The particularly smooth surface makes cleaning much easier, while the stable, dimensionally stable construction ensures durability and visual precision.

Hygienic stainless steel surfaces

Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

Corner bumpers

The corner bumpers protect the body at the exposed points of the equipment from damage caused by bumping or impact. The plastic construction on the chassis provides solid protection for the trolley.

Integrated push handles

The sturdy polymer upper bumpers provide reliable protection against damage and also act as ergonomic push handles. This well thought-out design enables safe handling in hectic everyday working life.

Thermal separation between well and compartments

Thanks to the thermal insulation between well and compartments, you can transport hot and cold food independently and keep them hot or cold respectively.

Deep-drawn stainless steel beads

The deep-drawn stainless steel beading in the side walls provides a hygienic and stable support for GN containers, trays and grids. The seamless design without undercuts ensures optimum cleanability.

Sturdy sliding lid

The robust sliding lid with automatic locking mechanism ensures convenient handling and reliable protection against condensation and soiling. The smooth-running mechanism enables easy operation and ensures long-lasting functionality in professional commercial kitchens.

Project _____

Order _____

Quantity _____

Date _____



Heated cupboard compartments

Heated wells

foil heating

The foil heating is bonded to the carrier medium over a large area. The heat is transferred very efficiently and evenly thanks to the large-surface contact.

GENERAL TECHNICAL DATA

Rated capacity

Position	Rated capacity	Quantity
Basin	GN 1/1	3
Compartments	GN 1/1	15
Width actual	1.393 mm	
Depth actual	795 mm	
Height	1.061 mm	
Weight	134 kg	
Payload	200 kg	
Main material	Stainless steel	

WELL PROPERTIES

Number of wells	3
Well size	GN 1/1
Useful height of the wells	200 mm
Well radius	40 mm
Fill level marking	Yes
Drain construction	Ball valve

Food transport trolley with sliding lid 3×GN 1/1

OPERATION

Control elements			
Operation area	Operation element	Minimum adjustable temperature	Maximum adjustable temperature
Setting per compartment	Rotary knob	30 °C	80 °C
Setting per basin	Rotary knob	30 °C	95 °C
Additional	On/off switch		

SLIDE-IN PROPERTIES

Insertions construction	Beads
Insertion type	Lengthwise insertion

ELECTRICS

Power rated	3.450 W
Operational Current	15 A
Voltage rated	220 V
Frequency	50 Hz
IP code	IPX5
Protection class	Class I
Plug	Schuko plug
Plug holder	Blank socket
Connection cable	Spiral cable
Max. length of connection cable	1.600 mm

HOUSING PROPERTIES

Cart housing construction	Double-walled, insulated
Cover construction	Sliding lid
Number of doors	3
Door construction	Hinged doors
Door lock (closed)	Snap lock
Door lock (open)	None
Door lock (car wash position)	No

HEATING

Heat generator	Foil heating Tubular heating element
Heating technology	Heat radiation
Total heat output	3.450 W
Heat output per compartment	450 W
Recirculated air distribution	No
Heat output per GN unit/well	700 W
Heating time	30 m

Safety temperature limiter	Yes
----------------------------	-----

INTERIOR PROPERTIES

Compartment construction	
compartment	equipment
Compartment 1	Inserts
Compartment 2	Inserts
Compartment 3	Inserts
Interior/compartment material	Stainless steel
Construction of the middle panel	Partition wall with support beads

MOBILITY

Castor equipment	
castor_type	quantity
Swivel castor with lock	2
Fixed castor	2
Castor attachment	Bolt-on panel
Chassis suitability	Off-premises transport
Castor bearing type	Ball bearing
Castor housing material	Plastic
Wheel ø	125 mm
Type of tyre tread	Rubber – Standard
Wheels with thread guard	Yes
Design of the locks	Total lock
Suitable for transport cart washing devices	Not approved
Impact protection construction	Corner bumpers
Push handle construction	Push handles