

Plate dispenser fan-assisted heating up to 80°C Ø190-260 mm

Project _____

Order _____

Quantity _____

Date _____

Product code

0162967-01

Type

TE/UH 2/VS/19-26

FUNCTIONAL DESCRIPTION

Plate dispenser for storing ø 7.5-10. 2" (190-260 mm) round plates in two stacking compartments heated with circulating air. The Hupfer plate dispenser TE/UH 2/19-26 VS not only provides shorter heating times, but also more uniform crockery temperatures. In addition, adapting the diameter of the stacking compartment for smaller crockery diameters reduces any loss of heat. The installation height of 900 mm is the standard working height in food serving practices.



EQUIPMENT FEATURES

Hygienic stainless steel surfaces

Hygienic stainless steel surfaces ensure a low-germ environment. The smooth, non-porous structure can be cleaned quickly and without leaving any residue. This saves you time, reduces cleaning costs and meets strict hygiene standards – ideal for commercial kitchens and medical areas. Robust, durable and reliable in daily use.

High Manoeuvrability: 4 swivel castors, 2 with total locks

Four smooth-running swivel castors, two with total locks, enable precise manoeuvring in tight spaces and secure locking during operation. This equipment ensures optimal mobility while maintaining high directional stability and security.

Manually adjustable tension spring system

Ensures a constant dispensing height of loads – for ergonomic working, faster processes and consistent presentation in kitchens and clinics.

Constant pick-up height

The constant pick-up height enables ergonomic working and reduces physical strain. The consistent height accelerates workflows and increases work efficiency. Precise stacking and safe access are guaranteed at all times.

Integrated push handles

The sturdy polymer upper bumpers provide reliable protection against damage and also act as ergonomic push handles. This well thought-out design enables safe handling in hectic everyday working life.

Fan-assisted heating

The fan-assisted heating ensures rapid and even heat distribution throughout the interior by circulating air. It enables short heat-up times and consistent temperature conditions, which increases energy efficiency and supports hygienic, stable, and reliable operation across different applications.

Dispenser with Cover

The dispenser with transparent cover hood ensures hygienic protection and optimal visibility of dishes. Thanks to its robust polycarbonate construction with 3-point locking mechanism, it enables effortless operation with maximum stacking safety.

Tool-free adjustable plate guide

The plate guide can be quickly and easily adjusted to the respective crockery without tools. This ensures that the crockery is held securely, prevents breakage and thus saves costs.

GENERAL TECHNICAL DATA

Rated capacity

Position	Rated capacity	Quantity
Stacker with cover	Plates	166
Stacker without cover	Plates	144

Width actual 459 mm

Depth actual 610 mm

Height 1.072 mm

Weight 45 kg

Payload 140 kg

Main material Stainless steel

OPERATION

Control element On/off switch
Rotary knob

Minimum adjustable temperature 30 °C

Maximum adjustable temperature 115 °C

Plate dispenser fan-assisted heating up to 80°C

ELECTRICS

Power rated	1.500 W
Operational Current	6,5 A
Voltage rated	220 V
Frequency	50 Hz
IP code	IPX5
Protection class	Class I
Plug	Schuko plug
Plug holder	Blank socket
Connection cable	Spiral cable
Max. length of connection cable	1.800 mm

HOUSING PROPERTIES

Cover construction	Plastic cover
--------------------	---------------

HEATING

Heat generator	Tubular heating element
Heating technology	Convection
Recirculated air distribution	Yes
Safety temperature limiter	Yes

MOBILITY

Set of castors	2 swivel castors with brakes 2 swivel castors
Castor attachment	Bolt-on panel
Castor bearing type	Ball bearing
Castor housing material	Plastic
Castor housing colour	Grey
Wheel ø	125 mm
Type of tyre tread	Rubber – Standard
Wheels with thread guard	Yes
Design of the locks	Total lock
Impact protection construction	Corner bumpers
Push handle construction	Push handles

DISPENSER PROPERTIES

Adjustable stacking device	Yes
Number of stacking compartments	2
Dispenser construction	2 round stacking devices
Stack height	607 mm
Staple goods	Plates ø 190 – 260 mm
Dispenser platform construction	Wire holder for plates