



ELEVATION SERIES CUBE ICE MAKER CIMO825

Model:

□ CIMO825



CIMO825 ON B42

Features and Benefits

- 22.25" (565 mm) wide space-saving design.
- Produces up to 418 kg of ice per day.
- *Energy and Environment*
 - Exceeds new 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.
- *Sanitation*
 - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
 - Built in Agion® ensures unbeatable antimicrobial protection.
 - Smart LED light indicates machine status and when cleaning is required.
 - Simple, one-touch controls for sanitization and descaling.
 - BPA-free snap-in, snap-out dishwasher-safe components.
- *Unique Dual Exhaust* - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- *Universal Smart Harness™* control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

CIMO825 CUBE ICE MAKER

Ice Form

FULL CUBE DIMENSIONS	
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (mm)	10 x 22 x 22



CUBE

Bin Chart *Kits for Combining Wider Bins with Smaller Models*

ICE STORAGE BINS								
	Model No.	B25	B40	B42	B55	ICB230SC	B110	ICB460
	Capacity	110 kg	156 kg	160 kg	232 kg	232 kg	388 kg	460 kg
	Width	762 mm	762 mm	559 mm	762 mm	764 mm	1,219 mm	1,226 mm
Kits	CIMO825	BT55		Kit Not Required	BT55	BT55	N/A	BT460

Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIMO825	CD20B	CD200B

Note: All modular cube CIM units can be installed with manufacturer approved ozone delivery systems.


Ice Maker Warranty

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labour
Evaporator and Compressor	5 YEARS parts





CIMO825 CUBE ICE MAKER



Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".

Operating Requirements

	MINIMUM	MAXIMUM
		50Hz
Ambient Temp. Range Air	10 °C	43 °C
Water Temp.	4.4 °C	
Water Pressure	1.4 BAR	5.5 BAR

Dimensions

ALL MODELS	
W x D x H (mm)	565 x 616 x 683

Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage litres per 45 kg of Ice 32°C air/21°C water		kWH Used per 45 kg of ice @ 32°C air/21°C water	Watts Used Per Hr @ 32°C air/21°C water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Refrigeration Capacity per hour
		21°C air/10°C water (kg)	32°C air/21°C water (kg)	Potable	Condenser						
CIMO825A-49	Air	408	316	68	-	49	1440	220-240/50/1	10.8	16	14,350

* Daily ice production based on half cube configuration. When installing a CIM on a drink dispenser, the KCUBEDISPB MUST be used.

Notes:
 Number of Wires: 3 (including ground)
 Approx. Shipping Weight lbs (kg): 100
 Refrigerant Type: R449A