



ELEVATION SERIES CUBE ICE MAKER CIM1135

Model:

□ CIM1135



CIM1135 ON CIB230

Features and Benefits

- 30.25" (768 mm) wide space-saving design.
- Produces up to 425kg of ice per day.
- *Energy and Environment*
 - Exceeds new 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.
- *Sanitation*
 - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
 - Built in Agion® ensures unbeatable antimicrobial protection.
 - Smart LED light indicates machine status and when cleaning is required.
 - Simple, one-touch controls for sanitization and descaling.
 - BPA-free snap-in, snap-out dishwasher-safe components.
- *Unique Dual Exhaust* - Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- *Universal Smart Harness™* control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

CIM1135 CUBE ICE MAKER

Ice Form

Bin Chart Kits for Combining Wider Bins with Smaller Models

FULL CUBE DIMENSIONS	
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (mm)	10 x 22 x 22



CUBE

ICE STORAGE BINS								
	Model No.	B25	B40	B42	B55	ICB230SC	ICB460	B110
	Capacity	110 kg	156 kg	160 kg	232 kg	232 kg	460 kg	388 kg
	Width	762 mm	762 mm	559 mm	762 mm	764 mm	1,226 mm	1,219 mm
Kits	CIM1135	Kit Not Required		N/A	Kit Not Required		BT460	BPF-1

Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIM1135	CD20B	CD200B

Ice Maker Warranty

COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts


Note: All modular cube CIM units can be installed with the O₃-Matic™ Ozone Delivery System.




Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".



Dual Exhaust for Installation Flexibility



Operating Requirements

	MINIMUM	MAXIMUM
		50Hz
Ambient Temp. Range Air	10 °C	43 °C
Water Temp.	4.4 °C	
Water Pressure	1.4 BAR	5.5 BAR

Dimensions

ALL MODELS	
W x D x H (mm)	768 x 616 x 683

Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage litres per 45 kg of Ice 32°C air/21°C water		kWH Used per 45 kg of ice @ 32°C air/ 21°C water	Watts Used Per Hr. @ 32°C air/ 21°C water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
		21°C air/ 10°C water (kg)	32°C air/ 21°C water (kg)	Potable	Condenser						
CIM1135A	Air	425	374	68	-	52	1791	220-240/50/1	15.2	25	19,300

* Daily ice production based on half cube configuration.

Notes:
 Number of Wires: CIM1135: 3 (including ground)
 Approx. Shipping Weight kg: CIM1135A 105
 Refrigerant Type: R404A