


YCR-1

600mm Gas Auto-Refill Rice Roll Steamer



Specifications

- NAT GAS: 70 MJ/h, LP Gas: 70 MJ/h
- Supplied with Gas regulator (specify NAT or LP on order)
- Gas Inlet: 3/4" BSP Male
- 65mm from Left, 70mm from Rear, 150mm from Floor
- Water Inlet: 1/2" BSP Male
- 500mm from Left, 70mm from Rear, 150mm from Floor
- Main Drain: 1-3/4" BSP Female
- 110mm from Left, 70mm from Rear, 300mm from Floor
- Overflow Drain: 1" Hose
- 77mm from Left, 410mm from Rear, 170mm from Floor
- Working Height: 800mm
- Dimensions: 600 x 800 x 1300H @ 95kg
- Packed Dimensions: 640 x 900 x 1470H @ 115kg
- Heavy duty construction with 304 stainless steel external panels
- Stainless steel feet with 55mm height adjustment range



Must be installed by an authorised person in accordance with AS/NZS 3000.

Please note that specifications or design may be altered at any time without notice.

Luus Industries Pty Ltd | +61 3 9240 6822 | sales@luus.com.au | www.luus.com.au

Auto-Refill Rice Roll Steamer

- Efficient 70 MJ/h flame thrower with piezo, pilot & FFD
- Insulated heat exchange system
- Produces more steam with less gas consumption
- In-built auto-refill water system with stainless steel float
- Accessible refill tank chamber for easier cleaning and servicing
- 304 stainless steel 7 hole plate steamer
- Front gutter design for easy cleaning
- Zinc-aluminium alloy burner handles

Cleaning & Servicing

- Easy access to all parts & components from front

Options/Accessories

- Yum cha skirt and steam plate attachment
- 250 & 500mm wide clip on shelves (front)
- Joining caps & strips
- LH & RH side shields
- Rear castors (2 x rigid)
- Front castors (2 x swivel with brakes)

Warranty

- 1 Year Included + 1 Year Extendable upon registration

