

Freestanding

LIEBHERR

FKDv 4203

Forced-air display refrigerator
Comfort



| | |
|---|-------------------------------------|
| Gross/net capacity | 403/385 l |
| Ext. dimensions in mm (w/d/h) | 600/687/2010 |
| Int. dimensions in mm (w/d/h) | 456/516/1660 |
| Energy consumption in 365 days | 564 kWh |
| Climate class (energy directive) | CC2 |
| Temperature class (energy directive) | K4 |
| Climate class (safety standard) | 5 |
| Ambient temperature range | +10 °C to +40 °C |
| Refrigerant | R 600a |
| Connection Rating | 1.5 A |
| Frequency / voltage | 50 Hz / 220-240 V- |
| Heat output | 634 |
| Cooling system | forced-air |
| Defrosting | automatic |
| Temperature range | +2 °C to +12 °C |
| Housing material/colour | steel / white |
| Door material | glass |
| Liner Material | commercial grade moulded polystyrol |
| Type of Control | LED 7-segment display with buttons |
| Temperature display | external digital |
| Interior light | LED |
| Adjustable Shelving | 5 |
| Shelf material | wire shelves plastic-coated |
| Loading capacity 0.5L PET/facings 0.5L PET | 256/7 |
| Loading capacity 0.33L can/facings 0.33L can | 512/7 |
| Shelf loading | 45 kg |
| Handle | ergonomic slimline handle |
| Type of lock | mechanical |
| Self-closing door | yes |
| Door hinges | right, reversible on site |
| Gross/net weight | 85/78 kg |
| EAN-Nr. | 9005382264690 |