CookTek®

Product Name Counter-Top Double Hob Cooktop

Quantity

Item #





Note: Induction cooking requires the use of induction compatible (i.e. magnetic) pots and pans.



COUNTER > TOP

DOUB

Standard Features

- Portable tabletop design with stainless steel housing, heavy duty electronic components, and high impact, thick, glass-ceramic top engineered for use in commercial kitchens
- Available in front-to-back (F) or side-by-side (S)
- Each induction hob has its own separate controls for independent operation and functionality
- Control knob for ease of use and automatic power or temperature control
- Temperature allows for 27 precise temperature settings and 20 power cook settings
- Pan Maximizer feature achieves maximum heating of any induction compatible pan
- Microprocessor monitors vital components 120 times per second to check for overheating, power supply problems, and more. Cooktop shuts off and displays error codes enabling user to diagnose and correct minor problems
- LED display for precise user feedback
- Automatic pan detection allows for instant energy transmission to pan and almost no energy consumption when pan is not present
- Automatic shut-off feature prohibits overheating
- Integral grease filter and air baffle to ensure cleaner and cooler air intake
- Sloped front panel allows for easy viewing and operation
- Easy to clean glass-ceramic top surface

- Integral cooling fan keeps internal electronics cool
- Available in 5000 or 7000 watts (200-240VAC) - 2500 or 3500 watts per hob
- Three years parts and one year labour warranty
- Made in the USA*

Specifications

| Shall be a | CookTek counter-top double hol | cooktop. |
|------------|--------------------------------|----------|
| model | with a total kW rating of | |

Unit shall be manufactured in the United States and constructed of a stainless steel housing and a high impact, thick, glass-ceramic top.

Unit shall be equipped with a built-in microprocessor that performs precise temperature control, auto shut-off to prevent overheating, self-diagnostics, and a pan maximizer feature that ensures maximum heating of any induction compatible pan.

Unit shall have an adjustable electronic control with 20 power cook settings and 27 precise temperature settings.

| Unit shall operate on | power | with | integra |
|-----------------------|-------|------|---------|
| cord and plug (suppl | ied). | | _ |

Australian distributor: Stoddart Food Service Equipment www.stoddart.com.au

Phone: 1300 79 1954 Fax: 07 3345 6403

Email: cooktek@stoddart.com.au





COUNTER > TOP Note: Ambient air should not exceed 50°C/122°F. Dedicated the right to change or improve specifications without notice. Power Cord Length Packaged Dim. (mm Weight Dimensions (in) Power Range Warranty Packaged Dim. (in) Packaged Weight Dimensions (mm) Amperage **BTU** Comparison Power Requirements Model Number Plug Type Power Consumption Temperature Range 5000W (max, 2x2400W) 5000W (max, 2x2400W) 27.58" x 13.85" x 4.99" 200-240VAC, 50/60 Hz DOUBLE 85-500°F / 30-260°C 100-2400W per hob 200-240VAC, 1Ph 812 x 584 x 279 2 x 22,000 BTU Country Specific 45 lbs / 20.4 kg 31 lbs / 14.1 kg 700 x 351 x 126 32" x 23" x 11" 6 ft / 1.8 m 20A (max) MC2502F F Model HOB circuit required. 200-240VAC, 50/60 Hz 16.35" x 27.58" x 4.99' 85-500°F / 30-260°C COOKTOP 100-2400W per hob 200-240VAC, 1Ph Country Specific 812 x 584 x 279 $\frac{\omega}{\omega}$ 415 x 700 x 126 45 lbs / 20.4 kg $2 \times 22,000 \, BTU$ 32" x 23" x 11" Many local codes 6 ft / 1.8 m 20 (max) MC2502S lbs / 14.1 kg exist, and it is the Owner and Installer's responsibility to comply with MC2502F, MC2502S, MC3002F, MC3002S, MC3502F, MC C Specifications 3 years parts and one year labour 0 G 10 S Model G **Dimensions** inches 27.58 25.05 13.85 16.35 13.82 4.99 27.58" x 13.85" x 4.99' 7000W (max, 2x3500W) | 7000W (max, 2x3500W 200-240VAC, 50/60 Hz 85-500°F / 30-260°C 100-3500W per hob 200-240VAC, 1Ph 812 x 584 x 279 2 x 35,000 BTU Country Specific mm 31 lbs / 14.1 kg 700 x 351 x 126 45 lbs / 20.4 kg 32" x 23" x 11" 30A (max) 6 ft / 1.8 m MC3502F 636 35 351 temperature of 50°C/122°F exceed) ambient Cooling clearance: Requires maximum (do not (55mm) for front, sides, and Dedicated circuit required 200-240VAC, 50/60 Hz 6 85-500°F / 30-260°C 100-3500W per hob .35" x 27.58" x 4.99 200-240VAC, Country Specific 812 x 584 x 279 415 x 700 x 126 2 x 35,000 BTU 45 lbs / 20.4 kg $\overline{\alpha}$ 32" x 23" x 11" 6 ft / 1.8 m 30A (max) MC3502S lbs / 14.1 1Ph <u>6</u>

Phone: 1300 79 1954 Fax: 07 3345 6403 Email: cooktek@stoddart.com.au

Australian distributor: Stoddart Food Service Equipment www.stoddart.com.au