



PHOENIKS

FLEXICOMBI MAGIC PILOT MAXI 10.2 ELECTRIC MODEL NO: FKE102R_MP

MKN combi steamer FlexiCombi 20 tray GN 1/1, with MagicPilot operation system.


Product Advantages:

- MagicPilot – Robust, wear-free, capacitive true colour touch screen.
- Video assist – Interactive user assistance with clips featuring professional chefs.
- CombiDoctor – Self-diagnosis programme.
- GreenInside – Indicates the energy and water consumption for each cooking programme.
- AutoChef – Up to 350 individual cooking programmes and manual operating system.
- Durable hygienic cooking chamber and chamber door with insulated triple glazing.
- DynaSteam2 – It speeds up the cooking process and saves energy.
- Integrated heat exchanger.
- WaveClean – Automatic cleaning system (safe, easy, economical).
- USB interface.
- 3 years warranty parts and labour.

Installation requirements:

- Soft Water / Water supply / Connection to waste water provided by customer.
- If mineral content is high, reverse osmosis system may be advisable.

Capacity: Meals per day 150 - 200



Technical Data:

Width x Height x Depth (mm)	997 x 1060 x 799
Connected load (electrical) (kW):	30.5
Voltage (V) / EC:	415 3 phase AC
Recommended fuses (A):	3 x 50
Frequency range (Hz):	50
Soft Water connection:	DN 20 (R ¾" inside)
Water connection:	DN 20 (R ¾" inside)
Waterpressure (kPa):	200 - 600 (2 - 6 bar)
Drain connection:	DN 50
Gastronorm 1/1 (530 x 325 mm):	20 (max. 65 mm deep)
Gastronorm 2/1 (530 x 650 mm):	10 (max. 65 mm deep)
Plates Ø 28 cm	40
Plates Ø 32 cm – plate trolley :	40
Material housing:	1.4301
Material cooking chamber:	1.4404
Gross weight (kg):	180
Heat emission latent (W):	5279
Heat emission sensitive (W):	3519
Type of protection:	IPX 5

INDUSTRY KITCHENS

www.industrykitchens.com.au 1800 611 058



phoeniks.com.au

P- 1300 405 404

E- contact@phoeniks.com.au