


MKN combi steamer junior 6 tray, Gastronorm 2/3 with manual operation system.

Product Advantages:

- Hygienic rounded corners and cooking chamber door with insulated triple glazing.
- Saves energy due to low heat loss, work safety due to low outside temperature.
- 5 fan speeds, auto reverse fan for best cooking uniformity.
- Up to 100 individual cooking programmes can be stored in up to 6 steps.
- USB interface.
- High speed centrifugal steam generation technology with heat recovery.
- ClimaSelect – Humidity and temperature control measurement.
- WaveClean – Automatic cleaning system (safe, easy, economical).
- 3 years warranty parts and labour.

Installation requirements:

- Soft Water / Water supply / Connection to waste water provided by customer.
- If mineral content is high, reverse osmosis system may be advisable.



Technical Data:

Width x Height x Depth (mm)	550 x 819 x 611
Connected load (electrical) (kW):	5.2 or 3.5
Voltage (V) / EC:	415 3 phase AC or 240 1 phase AC
Recommended fuses (A):	3 x 20 or 1 x 15
Frequency range (Hz):	50
Soft Water connection:	DN 20 (R ¾" inside)
Water connection:	DN 20 (R ¾" inside)
Waterpressure (kPa):	200 - 600 (2 - 6 bar)
Drain connection:	DN 40
Gastronorm 2/3 (354 x 325 mm):	6 (max. 60 mm deep)
Plates Ø 28 cm:	6
Material housing:	1.4301
Material cooking chamber:	1.4301
Net weight (kg):	68
Heat emission latent (W):	936 / 630
Heat emission sensitive (W):	624 / 420
Type of protection:	IPX 5

