Scotsman Ice Systems

INDUSTRY KITCHENS
www.industrykitchens.com.au 1800 611 058

MOFFAT

NU Series Self Contained Dice Ice Machines – up to 45kg

NU 100 AS OX Dice cube 10g, 22mm x 22mm x 22mm

NUH 100 AS OX Half dice cube 6g, 10mm x 22mm x 28mm



Dice cube 10 g
W 22 x D 22 x H 22 mm



Half dice cube 6 g
W 10 x D 22 x H 28 mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 45kg daily production rate
- 20kg storage bin capacity
- Air cooled version
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Vertical evaporator spray-system technology
- XSafe - Natural Sanitation System
- Ergonomic access to ice with sliding disappearing door
- One touch cleaning for time and labour saving
- Resistant stainless steel exterior
- Easy access front condenser air filter
- Routine maintenance visible alarm light on front panel
- Includes removable air filter, ice scoop, water and drain hose


ICIM CE EAC WaterMark DVE agion LOA XSafe


Scotsman®
Ice Systems

INDUSTRY KITCHENS
www.industrykitchens.com.au 1800 611 058

NU Series Self Contained Dice Ice Machines – up to 45kg

NU 100 AS OX, NUH 100 AS OX





UNIT OF MEASUREMENT: **mm**

MOFFAT®
moffat.com.au

Australia
Moffat Pty Limited

Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9413 2400
wasales@moffat.com.au

Ice production per 24 hours
Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NU 100 AS OX	56	45	32
NUH 100 AS OX	50	45	32

Dimensions
Width: 600mm
Depth: 610mm
Height: 770mm (including feet)
Nett weight: 50kg
Packed weight: 60kg

Water consumption
Air cooled version: 3.2 litres per hour

Electrical rating
Air cooled version: 230-240V, 1P+N+E, 50Hz, 450W, 10A cordset supplied
No. Circuit wire: 3
Compressor: 780W
Energy consumption: 9.2kW/hr

Refrigerant type
R404a

Installation distance from wall
Rear 100mm
Sides 150mm
Operating requirement air temperature 10-43°C

Water connection requirements
Inlet connection: R ¾"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø ¾"

Important Notice:
Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.

24:7 Service Support

© Copyright Moffat Ltd
AU.SM.2001