





Classe 20 USB Tall - RC3G C20ASB BLK

RANCILIO CLASSE 20 ASB TALL 3 GROUP



STANDARD FEATURES

- Tall deck accommodates tall cups up to 145mm in height includes retractable tray for espresso cups
- Advanced Steady Brew (ASB) patented multi-boiler technology for outstanding temperature control
- X-Tea-program water dosages and temperature levels via touchscreen interface
- 4.3" touchscreen display with digital shot timer function, dedicated screen for each brew group
- · RGB lights identifying operating status
- ABM advanced boiler management for outstanding steam pressure control and recovery
- Ergonomic portafilter holder up to 21g capacity, comfortable all-day
- C-Lever quarter turn steam tap features two positions: purge (down) or fully open (up)
- · Ergonomic cool to touch steam wands
- Hydro hub integrated manifold for precise water delivery and
- Multifunction onboard computer and USB port for simple programming and data transfer
- · Independent water pump and steam pressure control gauges keep you in control
- · Built-in volumetric rotary vane water pump for simple and safe installation
- · Steam boiler pressure control with mechanical pressure stat
- · Automated cleaning programme simplifies your daily clean

OVERALL CONSTRUCTION

- · Hand rolled copper steam boiler 16 litre capacity
- Brushed stainless steel front and rear panels
- Anthracite black ABS nylon side panels
- Backflow valve on boiler and steam tap
- · Adjustable feet with optional extensions

CONTROLS

- Soft-touch keypads with 4 programmable drink dosing pre-sets for easy espresso preparation
- White LED backlights easy to read keypad buttons
- Two manual steam wands for frothing and steaming milk

CLEANING AND MAINTENANCE

- Stainless steel drip tray dishwasher safe
- Easy Clean manages the cleaning process of group heads to perform automatically
- Genuine cleaning products sold separately

INCLUDES

- 1x Single group handle
- 1 x Single filter basket 16g
- 2 x Double group handle
- 2 x Double filter basket 21g
- 1x Rubber blind filter disc
- 1x Group head cleaning brush
- · User manual / Warranty card

MATCHING PRODUCTS

















Classe 20 USB Tall - RC3G C20ASB BLK

RANCILIO CLASSE 20 ASB TALL 3 GROUP

TECHNICAL INFORMATION

Dimensions

Width: 1015mm Depth: 569mm Height: 550mm Nett weight: 85kg Boiler Capacity: 16 litres

ELECTRICAL

Power requirements: 240V, 1P+N+E, 50/60Hz, 6.73W, 32A cordset fitted Boiler Power: 3.75kW



WATER CONNECTIONS AND DRAINS

- 40mm PVC drain and waste trap 300mm upstand
- Fixed water supply connection
- Mains cold water 3/8" BSP male thread connection
- Flow pressure: 200kPa -500kPa, min 4L/min



Australia www.moffat.com.au New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

New South Wales

Telephone +61 2-8833 4111 nswsales@moffat.com.au

South Australia

Telephone +61 3-9518 3888 vsales@moffat.com.au

Queensland

Telephone +61 7-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone +61 8-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Christchurch

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz









In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice


Copyright Moffat Ltd AN.RAN.2301


RANCILIO WATER SPECIFICATION


Optimum Parameter	Measurement Range
TDS <135	Never more than 50 PPM more than to Total Hardness
Carbonate Hardness 50 ppm	40-90 ppm
Total Hardness 85 ppm	50-100 ppm
pH (ideal) 7	6.5 – 8.5
Chlorides CI -	< 30 ppm

INSTALLATION CLEARANCE

- · Allow 152.4mm / 6" clearance on all sides of the machine.
- Allow 609mm x 127mm / 24" x 5" for in-line filter. Filter can be mounted behind the machine or under the
- Allow a minimum of 3" (762 mm) clear space under filter to facilitate filter change.
- All services to be within 1m of machine placement
- Always refer to installation manual







Specifications may vary between models

