





Classe 7 USB Tall - RC3G C7EVO BLK IS

RANCILIO CLASSE 7 USB TALL 3 GROUP ISTEAM



STANDARD FEATURES

- Factory fitted automated steam wand for one touch milk steaming operation
- Independently programmable buttons can be set for both milk temperature and emulsion
- Tall deck accommodates tall cups up to 145mm in height includes retractable tray for espresso cups
- SB Steady Brew patented heat exchanger technology for outstanding temperature control
- T-Switch, 4 positioned temperature extraction setting for each grouphead upon installation
- Single hot water button with start/stop dosing for full control
- RGB lights identifying operating status
- ABM advanced boiler management for outstanding steam pressure control and recovery
- Ergonomic portafilter holder up to 21g capacity, comfortable all-day operation
- C-Lever quarter turn steam tap features two positions: purge (down) or fully open (up)
- · Hydro hub integrated manifold for precise water delivery and distribution
- · Multifunction onboard computer and USB port for simple programming and data transfer
- Independent water pump and steam pressure control gauges keep you in control
- · Built-in volumetric rotary vane water pump for simple and safe installation
- · Steam boiler pressure control with mechanical pressure stat
- Automated cleaning programme simplifies your daily clean

OVERALL CONSTRUCTION

- · Hand rolled copper steam boiler- 16 litre capacity
- Brushed stainless steel front and rear panels
- Anthracite black ABS nylon side panels
- Backflow valve on boiler and steam tap
- · Adjustable feet with optional extensions

CONTROLS

- Soft-touch keypads with 4 programmable drink dosing pre-sets for easy espresso preparation
- White LED backlights easy to read keypad buttons
- Two manual steam wands for frothing and steaming milk

CLEANING AND MAINTENANCE

- · Stainless steel drip tray dishwasher safe
- · Easy Clean manages the cleaning process of group heads to perform automatically
- Genuine cleaning products sold separately

INCLUDES

- · iSteam retrofit kit factory fitted
- 1x Single group handle
- 1 x Single filter basket 16g
- 3 x Double group handle
- 3 x Double filter basket 21g
- 1x Rubber blind filter disc
- 1x Group head cleaning brush · User manual / Warranty card

MATCHING PRODUCTS

















CLASSE 5 USB TALL 2 GROUP

CLASSE 5 USB TALL 3 GROUP

CLASSE 7 USB TALL 2 GROUP

CLASSE 7 USB TALL 2 GROUP ISTEAM

CLASSE 7 USB TALL 3 GROUP



Classe 7 USB Tall - RC3G C7EVO BLK IS

RANCILIO CLASSE 7 USB TALL 3 GROUP ISTEAM

TECHNICAL INFORMATION

Dimensions

Width: 1011mm Depth: 539mm Height: 520mm Nett weight: 85kg Boiler Capacity: 16 litres

ELECTRICAL

Power requirements: 240V, 1P+N+E, 50/60Hz, 6.75kW, 32A cordset fitted Boiler Power: 6kW



RANCILIO WATER SPECIFICATION

| Optimum Parameter | Measurement Range |
|----------------------------------|--|
| TDS <135 | Never more than 50 PPM more than to Total Hardness |
| Carbonate Hardness 50 ppm | 40-90 ppm |
| Total Hardness 85 ppm | 50-100 ppm |
| pH (ideal) 7 | 6.5 – 8.5 |
| Chlorides CI - | < 30 ppm |

WATER CONNECTIONS AND DRAINS

- 40mm PVC drain and waste trap 300mm upstand
- Fixed water supply connection
- Mains cold water 3/8" BSP male thread connection
- Flow pressure: 200kPa -500kPa, min 4L/min

MOFFA

Australia www.moffat.com.au New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

New South Wales

Telephone +61 2-8833 4111 nswsales@moffat.com.au

South Australia

Telephone +61 3-9518 3888 vsales@moffat.com.au

Queensland

Telephone +61 7-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone +61 8-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Christchurch

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz











In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice


Copyright Moffat Ltd AN.RAN.2301


INSTALLATION CLEARANCE

- · Allow 152.4mm / 6" clearance on all sides of the machine.
- Allow 609mm x 127mm / 24" x 5" for in-line filter. Filter can be mounted behind the machine or under the
- Allow a minimum of 3" (762 mm) clear space under filter to facilitate filter change.
- All services to be within 1m of machine placement
 - Always refer to installation manual









Specifications may vary between models

