





RS1 INVICTA - RS3G RS1 INV INX

RANCILIO SPECIALTY RS1 INVICTA 3 GROUP



STANDARD FEATURES

- 4.3" touchscreen interface and each group head with dedicated
- · Pre-infusion and post-infusion barista has control over the water pressure of the extraction process
- X-Tea program water dosages and temperature levels via the interface
- T-Switch, 4 positioned temperature extraction setting for each grouphead upon installation
- Cool touch steam wands ensure easy manoeuvrability safe operation
- Programmable Timer function will drain and auto renew steam boiler water daily
- SB Steady Brew patented heat exchanger technology for outstanding temperature control
- · ABM advanced boiler management for outstanding steam pressure control and recovery
- Barista LED lighting provides maximum visibility for your coffee extraction and drip tray
- Low profile body designed to maximise customer interaction and
- Ergonomic portafilter holder up to 21g capacity, comfortable all-day
- · Built-in volumetric rotary vane water pump for simple and safe installation

OVERALL CONSTRUCTION

- · Hand rolled copper steam boiler 16 litre capacity
- Fully insulated boiler saves up to 20% energy in standby mode
- Brushed stainless steel exterior panels can be easily removed for

CONTROLS

- · Backlit keypads with 4 programmable drink doses and purge or free flow function
- Variable steam lever features purge function and two programmable pressure settings
- Dual hot water buttons can be independently programmed for dose and temperature

CLEANING AND MAINTENANCE

- · Stainless steel drip tray dishwasher safe
- · Easy Clean manages the cleaning process of group heads to perform automatically
- Grid system removable cup tray grids keeps work area clean and dishwasher safe
- Rubber blind filter cleaning disc supplied
- · Genuine cleaning products sold separately

MATCHING PRODUCTS



RANCILIO SPECIALTY



CLASSE 5 USB TALL 1 GROUP



CLASSE 5 USB TALL 2 GROUP



CLASSE 5 USB TALL 3 GROUP









CLASSE 7 USB TALL 2 GROUP



RS1 INVICTA - RS3G RS1 INV BLK

RANCILIO SPECIALTY RS1 INVICTA 3 GROUP

TECHNICAL INFORMATION

Dimensions

Width: 1057mm
Depth: 600mm
Height: 450mm
Nett weight: 90kg
Boiler Capacity: 16 litres

ELECTRICAL

Power requirements: 240V, 1P+N+E, 50/60Hz, 5400W, 32A cordset fitted Boiler Power: 6450W



WATER CONNECTIONS AND DRAINS

Connection point: Mains cold water - 3/8" BSP

Flow pressure: 30-707 PSI

Drain: open gravity-drain with minimum 50mm/2" LD within

101mm/4of the machine

Hardness: 2-3 GPG (1 grain of hardness = 17.1 ppm) Water Quality: Water entering the machine should have a

water hardness level of 2-3 GPG at all times.

Always refer to installation manual

New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

MOFFR

Australia

www.moffat.com.au

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

New South Wales

Telephone +61 2-8833 4111 nswsales@moffat.com.au

South Australia

Telephone +61 3-9518 3888 vsales@moffat.com.au

Queensland

Telephone +61 7-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone +61 8-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Christchurch

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz









In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.


© Copyright Moffat Ltd AN.RAN.2301


RANCILIO WATER SPECIFICATION


Optimum Parameter	Measurement Range
TDS <135	Never more than 50 PPM more than to Total Hardness
Carbonate Hardness 50 ppm	40-90 ppm
Total Hardness 85 ppm	50-100 ppm
pH (ideal) 7	6.5 – 8.5
Chlorides CI -	< 30 ppm


INSTALLATION CLEARANCE

- Allow 152.4mm / 6" clearance on all sides of the machine.
- Allow 609mm x 127mm / 24" x 5" for in-line filter. Filter can be mounted behind the machine or under the counter.
- Allow a minimum of 3" (762 mm) clear space under filter to facilitate filter change.
- · All services to be within 1m of machine placement









Specifications may vary between models