

| RANGE   | CODE        | MODEL  | FUNCTION            |
|---------|-------------|--------|---------------------|
| MI - 90 | MAMCOOO3330 | CV94EG | Glassceramic Ranges |

ITEM

**2 ceramic hotplate boiling top on open stand**



| RANGE   | CODE        | MODEL  | FUNCTION            |
|---------|-------------|--------|---------------------|
| MI - 90 | MAMCOOO3330 | CV94EG | Glassceramic Ranges |

#### ITEM

**2 ceramic hotplate boiling top on open stand**



#### TECHNICAL SPECIFICATIONS

|                               |                   |
|-------------------------------|-------------------|
| WIDTH (mm):                   | 400               |
| DEPTH (mm):                   | 920               |
| HEIGHT (mm):                  | 900               |
| WEIGHT (Kg):                  | 43                |
| VOLUME (m <sup>3</sup> ):     | 0.5               |
| EL. POWER (kW):               | 8                 |
| VOLTAGE:                      | VAC400-3N         |
| INTERNAL BASE UNIT DIM. (mm): | 360x400(h)x900 mm |
| COOKING ZONES N°:             | 2                 |
| COOKING ZONES DIM. (mm):      | 2x Ø 300 mm       |
| COOKING ZONE DETAILS:         | 2x 4kW            |
| IP GRADE:                     | IPX5              |

#### DESCRIPTION




Freestanding glass ceramic electric boiling top, on open cabinet base, in AISI 304 stainless steel. 20/10 pressed steel top with anti-spill front edge, designed for flush alignment with hermetic seal supplied. Top designed to accommodate water column accessory. 6 mm thick glass ceramic cooking surface hermetically sealed to the top and designed to create 2 independent cooking zones, each with underlying 4 kW Ø 300 mm radiant elements to reach maximum temperature of 400°C in 3 min. Glass dimensions 350x700 mm. The cooking zones are marked by screen printed circles on the glass-ceramic surface and equipped with residual heat indicators. Energy regulator for heat control with shape designed to prevent water infiltration, with integral indicator lights for instant recognition of appliance operation. Hotplates equipped with automatic reset safety thermostat that trips if the appliance is switched on with an unsuitable pan or no pan at all. IPX5 water-resistant rating. Appliance equipped with stainless steel adjustable feet.



| RANGE   | CODE        | MODEL  | FUNCTION            |
|---------|-------------|--------|---------------------|
| MI - 90 | MAMCOOO3330 | CV94EG | Glassceramic Ranges |

#### ITEM

**2 ceramic hotplate boiling top on open stand**



#### INSTALLATION SPECIFICATIONS

(E) Electrical Connection: **VAC400-3N 50/60Hz**

