



DIMENSIONS (mm)

400W X 920D X 900H

TECHNICAL DATA

Power Supply:	3NAC 400V 50Hz (Lead & Plug not included)
Electrical Power (kW):	8
Cooking Zones:	2
Cooking Zones Dimensions (mm):	300W X 300D
IP Grade:	IPX5
Internal Base Unit Dimensions (mm):	360W X 900D x 400H

SHIPPING DATA

Net Weight (Kg):	54
Shipping Weight:	TBA
Shipping Dimensions:	TBA

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.




Freestanding electric boiling top, on open cabinet base, in AISI 304 stainless steel. 20/10 pressed steel top with anti-spill front edge, designed for flush alignment with hermetic seal supplied. Top designed to accommodate water column accessory. Appliance comprising 2 cast-iron 300x300 mm square hotplates, hermetically sealed to the top, each with 4 kW output. Ergonomic knobs shaped to prevent water infiltration, equipped with integral indicator lights for instant recognition of operation and temperature. 7-position heat adjustment. Hotplates equipped with automatic reset safety thermostat that trips if the appliance is switched on with an unsuitable pan or no pan at all. IPX5 water-resistant rating. Appliance equipped with stainless steel adjustable feet.

STANDARD FEATURES

- 2mm thick pressed stainless top
- IPX5 water protection
- Modular design
- Enhanced Mareno knob with indicator lights to inform user of machine operating status
- NEW interlocking device & seal supplied with all units
- Space at rear for connections

OPTIONAL FEATURES

- Cabinet Doors
- Hygienic cabinet base with pressed runners
- Top only
- Refrigerated base
- 50mm stainless steel frame for counter installation
- Castor kit



Disclaimer: The images and line drawings provided are for reference only and may not exactly match the specifications of the equipment.

INSTALLATION SPECIFICATIONS

(E) Electrical Connection:

VAC400-3 50/60Hz