

Technical data sheet

M-iClean UL

M007DWUC10M3-40

Execution for: Australia

Utensil washer

Alternating current: 1N PE 230V 50Hz

Fresh water line: Soft hot water 0-3°dH

INDUSTRY KITCHENS

www.industrykitchens.com.au 1800 611 058


© MEIKO 2019

Sample illustration

Technical data

Rack capacity/h (theoretical)	40 / 30 / 15 racks/h
Programme cycle time	90 / 120 / 240 s
Rack dimension	500 x 600 (500) mm
Entry height	435 mm
Dimensions (W x Hmin x D)	600 x 855 x 680 mm
Electrical feeding cable	Alternating current 1N PE 230V 50Hz* nominal capacity: 2.7 kW nominal current: 15.5 A
Local fuse protection	16 A
Protection class of the machine	IP X4
Equipment	Control system MIKE CPU4 Bluetooth interface for wireless communication Leakage detector Boiler safety device Automatic self-cleaning when tank is drained Roller base 35 mm
Fresh water line	Air gap 'AB' in accordance with EN 1717 with booster pump
Fresh water supply	Minimum flow pressure 60 kPa / 0.6 bar in front of solenoid valve Maximum pressure: 500 kPa / 5.0 bar Max. supply water temperature 60 °C
Flow rate	3 l/min
Final rinse water quantity	2.8 liters/cycle, variable
Boiler	Contents: 7.9 l Heater: 2.00 kW Temperature: 83 °C Tank / boiler locked

Technical data sheet

Wash tank	Filling: 11.0 l Heater: 2.00 kW Temperature: 60 °C
Wash pump, with frequency converter	Performance: 0.40 kW
Dosing of rinse aid	Hose pump (24 V) with time control and suction lance
Detergent dosage	Hose pump (24 V) with time control and suction lance
Material	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4571
Heat emission	for 20 programme cycles/h total: 2.1 kW perceptible: 1.4 kW latent: 0.7 kW
Ventilation flow rate	540 m ³ /h
Steam emission	1.0 kg/h
Emission sound pressure level at the workplace (LpA)	62 dB
Net / gross weight	79.0 kg / 91.5 kg (standard packaging)
Packaging dimensions (W x H x D)	700 x 1050 x 770 mm (standard packaging)

*Note:

Electrical equipment suitable for supply voltage:

3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)

1N PE 230 V 50 HZ (1N PE 220-240 V 50 Hz)