


Reduce waste and increase profits by managing your busiest times and extending the life of your fried foods during offpeak times. With its versatile divider system, the Merco CrispyMax™ can keep a variety of fried products at their peak serving temperature. Internally controlled air temperature is directed over and through fried foods using Therma-Lock™ technology to maintain optimum product temperature and crispness, extending product retention.

STANDARD FEATURES


- Therma-Lock™ technology insures constant circulation of hot air over and through food to control moisture and maintain crispness
- Electronically controlled fan speed and temperature sensing ensure consistent performance across a range of voltages
- Electronically controlled air temperature and air flow for optimum holding environment
- Low-profile design allows for flexible installation. No overhead heating elements required.
- Removable food tray and crumb tray for easy cleanup
- On/Off Switch with LED indicator
- Heavy duty stainless steel construction
- Available in Single, Double or Triple Lane models - designed to fit industrystandard fry scoop
- Removable/Adjustable dividers
- Single Lane (none provided)
- Double Lane (one provided)
- Triple Lane (two provided)
- Merco warranty: 1 year parts and labour

OPTIONAL FEATURES


- Additional stainless steel dividers (p/n 2602434)
- Custom scoop-holding divider (p/n 2602572)
- Stainless Steel Bridge for adjacent fryer (p/n 2602576)
- Drop-In Accessory Kit (coming soon!)




Front - XMCG1027NNN




Front - XMCG1827NNN




Front - XMCG2727NNN




Top - XMCG1027NNN



Top - XMCG1827NNN



Top - XMCG2727NNN



Side View - All models

SPECIFICATIONS

Model Number	Desc.	Height	Width	Dpth	Volts	Hz	Watts	Amps	Plug Type	Ship Wt
XMCG1027NNN	Single Lane	183mm	254mm	635mm	240	50	1275	5.4	10A	16kg
XMCG1827NNN	Double Lane	183mm	470mm	635mm	240	50	2530	10.6	15A	26kg
XMCG2727NNN	Triple Lane	183mm	686mm	635mm	240	50	3815	15.9	20A Not Plugged	36kg

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.