

# Curlflow®

**HCS1114, HCS12518**

**HCS1418**

**Bread Slicer**

**MOFFAT®**

**INDUSTRY  
KITCHENS**

[www.industrykitchens.com.au](http://www.industrykitchens.com.au) 1800 611 058

## Product Features

- Twin frame unit fitted with two independent motors
- Independent variable weighted pushers designed to suit soft and crusty breads
- Loaf guides incorporated into rear chute
- Emergency stop button
- Green start and red stop buttons
- V-Type stainless steel bagging spade
- Exit table with adjustable lexan loaf guides
- Various slice thickness available



HCS1114

Moffat offers a comprehensive range of equipment manufactured locally or sourced from some of the world's industry leading brands. With an extensive sales and support network, our products are backed by the knowledge and experience gained from a long and rich history in the baking industry.

Moffat bread slicers are available in a range of slice thicknesses to suit your slicing needs. Featuring long stroke slicing technology made possible by our treadle drive system, our bread slicers offer quiet and vibration free operation with the highest consideration for operator safety.

## HCS1114, HCS12518 HCS1418 Bread Slicer

| Models   | Slice Thickness (mm) | External Dimensions (mm) |           |            | Kilowatt | Weight (kg) |
|----------|----------------------|--------------------------|-----------|------------|----------|-------------|
|          |                      | With (A)                 | Depth (B) | Height (C) |          |             |
| HCS1114  | 11 - 14              | 1150                     | 950       | 1780       | 1.0kW    | 300         |
| HCS12518 | 12.5 - 18            | 1150                     | 950       | 1780       | 1.0kW    | 300         |
| HCS1418  | 14 - 18              | 1150                     | 950       | 1780       | 1.0kW    | 300         |

### Electrical Requirements

400-415V, 3P+N+E, 50Hz

### Additional Information

Power outlet to be located a minimum of 1500mm off the floor

Various thickness options available on request

[moffat.com.au](http://moffat.com.au)

[moffat.co.nz](http://moffat.co.nz)

Australia

[moffat.com.au](http://moffat.com.au)

Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road

Mulgrave, Victoria 3170

Telephone +613-9518 3888

Facsimile +613-9518 3833

[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

New South Wales

Telephone +612-8833 4111

[nswsales@moffat.com.au](mailto:nswsales@moffat.com.au)

South Australia

Telephone +613-9518 3888

[vsales@moffat.com.au](mailto:vsales@moffat.com.au)

Queensland

Telephone +617-3630 8600

[qldsales@moffat.com.au](mailto:qldsales@moffat.com.au)

Western Australia

Telephone +618-9413 2400

[wasales@moffat.com.au](mailto:wasales@moffat.com.au)

New Zealand

[moffat.co.nz](http://moffat.co.nz)

Moffat Limited

Rolleston

45 Illinois Drive

Izone Business Hub

Rolleston 7675

Telephone +64 3-983 6600

Facsimile +64 3-983 6660

[sales@moffat.co.nz](mailto:sales@moffat.co.nz)

Auckland

Telephone +64 9-574 3150

[sales@moffat.co.nz](mailto:sales@moffat.co.nz)



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice. This specification sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.

© Copyright Moffat Ltd  
AN.C0121

