## Pegasus Series 1/1 Preparation GN

## **Food Preparation**



Gastronorm Storage

The Pegasus range of premium food prep fridges are designed to keep food cool and fresh in hot kitchens. A constant flow of chilled air maintains consistent temperatures. With hygienic easy clean prep areas and removable sliding night covers, Pegasus offers you high food safety.









PG250 Prep

PG400 Prep

PG550 Prep

Standard finishes: Stainless steel
Standard models: 2, 3 & 4 solid door









## **Quick Guide**


Pegasus Series 1/1 Preparation GN				
Premium build quality	<b>⊘</b>			
Gastronorm 1/1 (GN)	<b>⊘</b>			
Busy - heavy duty kitchens				
SKOPE premium controller	<b>⊘</b>			
Remote available	<b>Ø</b>			
Customisable	<b>⊘</b>			
Standard Features	Benefits			
SKOPE premium controller	Easy to use with pre-programmed features			
Self closing, self sealing doors	Convenient & reliable			
Front breathing refrigeration system	Built in design to save space			
Fan forced ducted airflow	Consistent temperature for food safety			
Heated fascia	Eliminates condensation			
Door activated interior LED lighting	Easy to find stored products			
Key locks on all doors	Extra security			
Sliding night covers	Convenient & easy to remove for access			
Options				
<ul><li>White or black powdercoat</li><li>Full powdercoat colour range</li></ul>	<ul><li>Extra shelf &amp; slides/clips</li><li>Plinth mounting</li></ul>			
Remote	1-6 pans & dividers			
<ul><li>R/H services</li><li>2 drawers per door</li></ul>	<ul> <li>Removable insulated night lid</li> <li>Stainless steel punched shelves</li> </ul>			
·	Same Steel partered Steel Co.			
1 year extended warranty				

Specifications	PG250	PG250 Prep		PG400 Prep		PG550 Prep	
Fridge/Freezer - doors	Fridge - 2 door		Fridge - 3 door		Fridge - 4 door		
Self Contained/Remote	Self Contained	Remote	Self Contained	Remote	Self Contained	Remote	
Model ID	PG250Prep	PG250Prepr	PG400Prep	PG400Prepr	PG550Prep	PG550Prepr	
External							
Dimensions (W x D x H mm)	1331 x 700 x 751	1181 x 700 x 751	1799 x 700 x 751	1649 x 700 x 751	2267 x 700 x 751	2117 x 700 x 751	
Total floor area (m²)	0.93	0.83	1.26	1.15	1.59	1.48	
Weight (kg)	160	130	175	145	175	160	
Door	So	Solid		Solid		Solid	
Electronic Controller	Ye	es	Y	·es	Yes		
Remote duty (Watts @ SST)	N/A	500 @ -10°C	N/A	706 @ -10°C	N/A	706 @ -10°C	
Breathes from / Expels air to	Front	/ Front	Front	/ Front	Front / Front		
Sign	N	No		No		No	
Cabinet construction	Stainle	Stainless steel		Stainless steel		Stainless steel	
Drainage (plumbing required)	No	Yes	No	Yes	No	Yes	
Locks as standard	Ye	Yes		Yes		Yes	
Can be plinth mounted	Ye	Yes		Yes		Yes	
Supplied with legs & castors	Ye	Yes		Yes		Yes	
Internal							
Gross volume (litres)	26	260		410		560	
Lighting	1 x T8	1 x T8 LED		2 x T8 LED		2 x T8 LED	
Well capacity	4 x 1-3 0	4 x 1-3 or 8 x 1-6		7 x 1-3 or 14 x 1-6		10 x 1-3 or 20 x 1-6	
No. of shelves (per door)	2	2		2		2	
Shelf design	Plastic co	Plastic coated wire		Plastic coated wire		Plastic coated wire	
Total shelf area (m²)	0.	0.63		0.94		1.25	
Coved floor	Ye	Yes		Yes		Yes	
Internal material	Stainle	Stainless steel		Stainless steel		Stainless steel	
Performance							
Temperature range	ı°C t	1°C to 5°C		1°C to 5°C		1°C to 5°C	
Maximum ambient temperature	30	30°C		30°C		30°C	
Climate Class rating	4	4		4		4	
Refrigerant / charge	R134a / 800g	Specify	R134a / 800g	Specify	R134a / 800g	Specify	
Electrical							
Electrical power (kW)	0.9	0.11	1.2	1.12	1.13	1.17	
Current draw (Amps)	3.77	3.71	5.09	4.70	5.26	4.86	
10 Amp 3 pin plug	Ye	Yes		Yes		Yes	
Light switch on controller	N	No		No		No	

## Line Drawings







Cabinet height variation:
With supplied castors, add 95mm-120mm
With supplied adjustable legs, add 150mm-180mm

The product information presented is for guideline purposes only. Always refer to the latest product specification sheet for accuracy and detail, and allow for dimensional tolerances (see glossary).