# Pegasus Series 2/1 Pizza GN

### **Food Preparation**







PG500 Pizza

PG800 Pizza

Standard finish: Stainless steel
Standard models: 2 & 3 solid door








## **Quick Guide**


Pegasus Series 2/1 Pizza GN			
Premium build quality	<b>⊘</b>		
Gastronorm 2/1 (GN)	<b>⊘</b>		
Busy - heavy duty kitchens	<ul><li>⊘</li><li>⊘</li><li>⊘</li><li>⊘</li></ul>		
SKOPE premium controller	<b>⊘</b>		
Remote available	<b>⊘</b>		
Customisable	<b>⊘</b>		
Standard Features	Benefits		
SKOPE premium controller	Easy to use with pre-programmed features		
Self closing, self sealing doors	Convenient & reliable		
Front breathing refrigeration system	Built in design to save space		
Fan forced ducted airflow	Consistent temperature for food safety		
Heated fascia	Eliminates condensation		
Lift off perspex lids	For easy product viewing and cleaning		
Key locks on all doors	Extra security		
Options  White or black powdercoat Full powdercoat colour range	<ul> <li>Plinth mounting</li> <li>1-6 pans &amp; dividers</li> </ul>		
• Remote	Racks & trays		
<ul><li>R/H services</li><li>2 drawers per door</li></ul>	<ul> <li>Removable insulated night lid</li> <li>Stainless steel punched shelves</li> </ul>		
Extra shelf & slides/clips			
• 1 year extended warranty			

### Specifications PG500 Pizza PG800 Pizza

Fridge/Freezer - doors	Fridge - 2 door		Fridge - 3 door	
Self Contained/Remote	Self Contained	Remote	Self Contained	Remote
Model ID	PG500Pizza	PG500Pizzar	PG800Pizza	PG800Pizzar
External			· ·	
Dimensions (W x D x H mm)	1750 x 830x 900		2435 x 830 x 900	
Total floor area (m²)	1.45		2.02	
Weight (kg)	145	130	160	145
Door	Solid		Solid	
Electronic controller	Yes		Yes	
Remote duty (Watts @ SST)	N/A	706 @ -10°C	N/A	706 @ -10°C
Breathes from / Expels air to	Front	/ Front	Front /	Front
Sign	No		No	
Cabinet construction	Stainless steel		Stainless steel	
Drainage (plumbing required)	No	Yes	No	Yes
Locks as standard	Yes		Yes	
Can be plinth mounted	Yes		Yes	
Supplied with legs & castors	Yes		Yes	
Internal				
Gross volume (litres)	480		750	
Lighting	N/A		N/A	
Well capacity	9 x 1-3 or 18 x 1-6		13 x 1-3 or 26 x 1-6	
No. of shelves (per door)	2		2	
Shelf design	Plastic coated wire		Plastic coated wire	
Total shelf area (m²)	1.27		1.91	
Coved floor	Yes		Yes	
Internal material	Stainless steel		Stainless steel	
Performance				
Temperature range (adjustable up to 15°C)	1°C to 5°C		1°C to 5°C	
Maximum ambient temperature	30°C		30°C	
Climate Class rating	4		4	
Refrigerant	R134a / 800g	Specify	R134a / 800g	Specify
Electrical				
Electrical power (kW)	0.8	0.1	0.9	0.2
Current draw (Amps)	3.43	0.49	3.54	0.61
10 Amp 3 pin plug	Yes		Yes	
Light switch on controller	N	lo	No	

#### Line Drawings





Cabinet height variation:
With supplied castors, add 95mm-120mm
With supplied adjustable legs, add 150mm-180mm
With optional plinth, add 34mm

The product information presented is for guideline purposes only. Always refer to the latest product specification sheet for accuracy and detail, and allow for dimensional tolerances (see glossary).