

## Two Solid Swing Door SlimLine

**Range:** BackBar

**SKOPE ID:** SL002

**Dimensions:** 1580 mm (W) × 590 mm (D) × 830 mm (H)\*

**Capacity:** 290 L

\* Height with castors is adjustable from 820 to 835.

**Project:** \_\_\_\_\_

**Item #:** \_\_\_\_\_



A solid door under-bar fridge designed to merchandise ready-to-serve cold beverages and food in bars, restaurants, clubs, pubs, and cafés. With M1 compliance it is engineered to serve cold food and drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



**Warranty**




**Natural Refrigerant**



**GEMS**



**SKOPE-connect**



### Cabinet

Type	SlimLine		
Finish	Powdercoated galvanised steel or stainless steel		
Insulation	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso Pentane (C5H10/C5H12)	
Doors	Type	Solid swing door (self-closing, foamed, lockable)	
	Opening Size	Height (mm)	538
		Width (mm)	511
Shelving	Four adjustable height, plastic-coated wire shelves 4 x inner shelf (547W x 440L)		
Lighting*	1 x 16 W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling		

### Dimensions†

	External	Internal	Packed
Width (mm)	1580	1120	TBC
Depth (mm)	590	475	TBC
Height (mm)	830 (std. castors)	545	TBC
	725 (plinth mount)		
Weight (kg)	166		TBC
Capacity (L)	290		
Footprint (m <sup>2</sup> )	0.93		

### Ventilation (mm)

Top	Sides	Rear
Not required	Not required	Not required

### Product Loading

	Facing	Loading
330 ml can	32	192
600 ml bottle	28	168

\* Accessible via the free SKOPE-connect™ app.

† Allow for dimensional tolerances when installing the cabinet(s).

### Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)	
Rated Ambient Temperature	40°C/40% relative humidity	
Maximum Ambient Temperature (°C)	40	
Sound Level (dB(A))	Standard	Less than 66
	Hush Mode*	Less than 62

### Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	7	
Product Temperature Class	M1 (-1 to 5°C)	
Total Energy Consumption	1.57 kW h/24 h	
Annual Running Costs	\$172 (@ \$0.30/kW h)	

### Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply	
Cord	1.9 m power cord with 3-pin, 10 amp plug	
Current draw (A)	2.6	

### Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)		
System Type	Removable cartridge		
Cartridge Weight (kg)	24		
Refrigerant/Charge	R290/81 g		
Nominal Capacity (W)	650		
Heat Rejection (W)	Average	65	Peak 85
Remote Duty	n.a.		
Defrost Type	Off-cycle		
Drainage	No plumbing required		



SL.2.SSW  
on the SKOPE website