

ALFA410XAU



Family

Subfamily

Power supply

Oven type

Oven control

Trays capacity

Power supply

Adjustable feet

Product dimensions WxDxH

Maximum depth with open door

Ovens

Convection oven 4 trays EN 600x400 mm or GN1/1

Electric

One function

Mechanical

4 trays EN 600x400 mm, GN1/1 (min. H 20 mm)

230 V~ / 50 Hz / 15 A / 3,1 kW

Yes

798x747x563 mm

1145 mm



Distribution

Industries

Bar / Cafeterias / Bistros /
Wine bars / Pubs; Hotels;
Restaurants; Bakeries /
Pastry shops; Butcher
shops / Delicatessens;
Catering; Care facilities ;
Commercial food services;
Grocery shops / Food retail

Suggested for

Bars/Cafes

Aesthetics

Door with stainless
steel stripes

Yes

Colour

Stainless steel

Front panel

Yes

Logo

Serie

Smeg printed

Alfa

Controls

Timer setting range

1-60 minutes + endless

Options

Solutions

K4610X

Electrical Connection

Compatible Accessories




3743
Flat aluminium tray



3751
Flat perforated aluminium tray




3805
Flat chrome-plated wire grid



3810
Corrugated grid for baguettes



3927
Air flow reducer kit



RGN11-420-2
Support rack for GN 1/1 flat trays,
suitable for ALFA420/425/410 models



RUTVL
Wheels kit for all oven table models
(4pcs)



SVRPP420-625
Connector kit for two stacked
ALFA420+420 or ALFA420+625
models and hood



T11TH20
2cm height GN1/1 non-stick tray for
Galileo professional




T11TH40
4cm height GN1/1 non-stick tray for
Galileo professional




T11XH20
2cm height aluminium GN1/1 tray for
Galileo professional



T11XH65
6,5cm height aluminium GN1/1 tray
for Galileo professional



TF11XH2
Perforated aluminium GN1/1 tray for
Galileo professional



TMF11TH2
GN 1/1 non-sticking microperforated
tray

Symbols glossary



Electric



...

Benefit (TT)

Mechanical control panel

Ease of use and effortless control of the essential cooking parameters

The control panel, equipped with practical knobs, allows for simple, intuitive, and effortless management of the main functions. Using the buttons, you can adjust the cooking time, temperature, and, in selected models, the level of humidification. By turning the knob to position 1, steam will be delivered until it is released.

In multifunction ovens with a mechanical control panel, there is also a dedicated button for selecting different oven functions based on the desired cooking mode.

Clip-open

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.