

Thermaster 2 Frameless Glass Door Multideck Display Fridge - DC-125BS

Quick Overview

- Gross Volume: 1292L
- **Sleek Edition front**
  -Concealed door hinges for a clean, minimalist front.
  -Cap-free frame: top and bottom plastic end caps removed.
  -Expanded glass height â€” more glass, less frame.
  -Matte-finish solid aluminium handle, scratch-resistant satin surface.
  -Refined front cover with engineered rounded-square ventilation.
- **Merchandising and visibility**
  -Contents are displayed from the front and two sides.
  -Energy-saving design: magnetic LED lighting on the top and integrated lighting on each shelf.
  -Bright, clean, and anti-glare.
  -Adjustable shelf angle: 0Â ° / 7Â ° / 14Â ° .
  -Low-E glass.
- **Energy-saving design**
  -EC fans and anti-reflex glass doors minimise energy consumption.
  -Self-closing doors.
  -Natural, eco-friendly refrigerant.
  -8 Star GEMS rating
- **Refrigeration and control**
  -Fan-forced cooling.
  -Digital temperature control and read-out.
  -Temperature range -1 to +5Â ° C at 25Â ° C / 60% RH ambient.
  -Suitable for dairy and milk drinks, packed meat, vegetables, fruits, and hamburgers
- **Line-ups, footprint and servicing**
  -Designed for multiplexing with building joining kits included.
  -Smaller base design to reduce floor footprint.
  -Pull-out condensing unit for easiest after-sales operation.
- **Display Area**: 3.14 mÂ²

Description

Thermaster 2 Frameless Glass Door Multideck Display Fridge - DC-125BS

The Thermaster DC Series is a premium panoramic **frameless glass door multideck display fridge** designed for supermarkets, convenience stores, and grocery retailers. Available in M1 refrigerated models, the DC Series offers flexible line-up configurations, fan-forced refrigeration and outstanding product visibility to maximise merchandising performance.

Key Features

- Gross Volume: 1292L
- **Sleek Edition front**
  -Concealed door hinges for a clean, minimalist front.
  -Cap-free frame: top and bottom plastic end caps removed.
  -Expanded glass height — more glass, less frame.
  -Matte-finish solid aluminium handle, scratch-resistant satin surface.
  -Refined front cover with engineered rounded-square ventilation.
- **Merchandising and visibility**
  -Contents are displayed from the front and two sides.
  -Energy-saving design: magnetic LED lighting on the top and integrated lighting on each shelf.
  -Bright, clean, and anti-glare.
  -Adjustable shelf angle: 0 ° / 7 ° / 14 ° .
  -Low-E glass.
- **Energy-saving design**
  -EC fans and anti-reflex glass doors minimise energy consumption.
  -Self-closing doors.
  -Natural, eco-friendly refrigerant.
  -8 Star GEMS rating
- **Refrigeration and control**
  -Fan-forced cooling.
  -Digital temperature control and read-out.
  -Temperature range -1 to +5 ° C at 25 ° C / 60% RH ambient.
  -Suitable for dairy and milk drinks, packed meat, vegetables, fruits, and hamburgers
- **Line-ups, footprint and servicing**
  -Designed for multiplexing with building joining kits included.
  -Smaller base design to reduce floor footprint.
  -Pull-out condensing unit for easiest after-sales operation.
- **Display Area**: 3.14 m^2

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Are Registered Within 14 Days Of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Colorbond
Gross Volume	1292L
Max Ambient Temperature	25°C, 60%RH
Temperature Range	-1 to +5 ° C
Form Factor	Upright
Net Weight (Kg)	253
Width (mm)	1250+60
Depth (mm)	740
Height (mm)	2058
Packing Width (mm)	1417
Packing Depth (mm)	770
Packing Height (mm)	2141
Power	240V, 550W/10A
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Are Registered Within 14 Days Of Invoice