Thermaster 2 Frameless Glass Door Multideck Display Freezer - DC-125BTFG

Quick Overview

- Gross Volume: 1062L
- Net Volume: 829L
- **Frameless full glass doors**
  -Frameless full glass doors provide clear product visibility.
  -LED lighting highlights products clearly.
  -Matte black finish suits premium retail spaces.
  -Standard price strip for retail display use.
- **Stable frozen holding**
  -Air curtain cooling maintains stable cabinet temperatures.
  -Temperature range: -18 to -15Â ° C at 25Â ° C / 60% RH ambient.
  -60mm insulation helps improve thermal retention.
  -Light and door heating switches allow separate control.
  -Door stop and self-closing function help reduce energy loss.
- **Energy and refrigerant**
  -SECOP inverter compressor supports quiet, energy-efficient operation.
  -R290 natural refrigerant, compliant with Australian standards.
  -5 Star GEMS rating
- **Easier servicing and cleaning**
  -Automatic defrost with hot gas and heater tube reduces manual maintenance.
  -Pull-out condenser and front-mounted compressor allow easier servicing.
  -Stainless steel inner base for durability and easy cleaning.
- **Display and placement**
  -4 wire shelves and bottom basket provide flexible product display.
- **Adjustable shelf angle 0 Â ° ¦ 7 Â ° ¦ 14 Â °**
  -1.5-inch castors with levelling feet for movement and stable placement.
- **Display Area**: 1.61 mÂ²

Description

Thermaster 2 Frameless Glass Door Multideck Display Freezer - DC-125BTFG

The Thermaster DC-BTFG range is a **frameless glass-door multideck display freezer** for supermarkets, convenience stores, cafés and food retailers. Full glass doors remove the frame from the shopper ' s sightline, so the product is what they see. Two, three, and four-door cabinets all hold -18 to -15 ° C and carry a 5 Star GEMS rating.

Multiplexable design supports seamless multi-unit installation, so cabinets can be joined into a continuous frozen run.

Key Features

- Gross Volume: 1062L
- Net Volume: 829L
- **Frameless full glass doors**
  -Frameless full glass doors provide clear product visibility.
  -LED lighting highlights products clearly.
  -Matte black finish suits premium retail spaces.
  -Standard price strip for retail display use.
- **Stable frozen holding**
  -Air curtain cooling maintains stable cabinet temperatures.
  -Temperature range: -18 to -15 ° C at 25 ° C / 60% RH ambient.
  -60mm insulation helps improve thermal retention.
  -Light and door heating switches allow separate control.
  -Door stop and self-closing function help reduce energy loss.
- **Energy and refrigerant**
  -SECOP inverter compressor supports quiet, energy-efficient operation.
  -R290 natural refrigerant, compliant with Australian standards.
  -5 Star GEMS rating
- **Easier servicing and cleaning**
  -Automatic defrost with hot gas and heater tube reduces manual maintenance.
  -Pull-out condenser and front-mounted compressor allow easier servicing.
  -Stainless steel inner base for durability and easy cleaning.
- **Display and placement**
  -4 wire shelves and bottom basket provide flexible product display.
- **Adjustable shelf angle 0 ° ¦ 7 ° ¦ 14 °**
  -1.5-inch castors with levelling feet for movement and stable placement.
- **Display Area**: 1.61 m^2

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Are Registered Within 14 Days Of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Colorbond
Gross Volume	1062L
Net Volume	829L
Max Ambient Temperature	25°C, 60%RH
Temperature Range	-18 to -15 ° C
Form Factor	Upright
Net Weight (Kg)	253
Width (mm)	125+110
Depth (mm)	740
Height (mm)	2058
Packing Width (mm)	1417
Packing Depth (mm)	770
Packing Height (mm)	2141
Power	240V, 800W/10A
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Are Registered Within 14 Days Of Invoice