



## Thermaster 12x1/3 GN pan Ventilated Refrigerated Saladette - TL1500TN-12P

### Quick Overview

The Ventilated Refrigerated Saladette is a high-performance chilled display unit designed for Australian cafes, delis, and commercial kitchens. Featuring HC-free refrigerant and energy-efficient operation, it ensures compliance with local environmental standards while reducing running costs.

Its ventilated refrigeration system maintains consistent temperatures for optimal food freshness, while the auto-defrost and tool-free magnetic gasket simplify maintenance. Built with 60mm thick insulation and self-closing doors, it delivers superior thermal efficiency even in high-ambient temperatures. Ideal for salads, dairy, and ready-to-eat foods, this unit supports GN pans (sold separately).

Â

### Key Features

- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Ventilated refrigeration compartment gives a better air circulation
- Auto defrosting and auto evaporation of condensation water
- Magnetic gasket can be replaced without any tools
- Insulation 60 mm thickness
- Self-closing doors
- Pans and pan covers must be used to ensure correct operating temperature
- Optional GN pans available
- Shelf: 2
- PAN GN1/3: 12

### Description

Thermaster 9x1/3 GN pan Ventilated Refrigerated Saladette - TL1200TN-9P

The Ventilated Refrigerated Saladette is a high-performance chilled display unit designed for Australian cafes, delis, and commercial kitchens. Featuring HC-free refrigerant and energy-efficient operation, it ensures compliance with local environmental standards while reducing running costs.

Its ventilated refrigeration system maintains consistent temperatures for optimal food freshness, while the auto-defrost and tool-free magnetic gasket simplify maintenance. Built with 60mm thick insulation and self-closing doors, it delivers superior thermal efficiency even in high-ambient temperatures. Ideal for salads, dairy, and ready-to-eat foods, this unit supports GN pans (sold separately).

#### Key Features

- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Ventilated refrigeration compartment gives a better air circulation
- Auto defrosting and auto evaporation of condensation water
- Magnetic gasket can be replaced without any tools
- Insulation 60 mm thickness
- Self-closing doors
- Pans and pan covers must be used to ensure correct operating temperature
- Optional GN pans available
- Shelf: 2
- PAN GN1/3: 12

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

## Your Shipping Specifications

---

Product Condition	New
Doors	2
Gross Volume	368L
Max Ambient Temperature	32°C, 60%RH
Temperature Range	+2 to +8 ° C
Width (mm)	1500
Depth (mm)	700
Height (mm)	800
Packing Width (mm)	1530
Packing Depth (mm)	730
Packing Height (mm)	901
Power	240V
Warranty	2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration