

REFRIGERATED INGREDIENT UNITS

GLASS CANOPY VRX1200/VRX1500/VRX1800

Product Specifications

- Interior and exterior stainless steel
- Glass supplied in kit form
- Ambient temperature 38° C
- Digital dixell controller
- Adjustable feet



Model Specifications

VRX1200	Takes 4 $\frac{1}{3}$ GN pans or 3 x $\frac{1}{3}$ and 1 $\frac{1}{2}$ pans not supplied	1200 x 395 x 435 mm	43kg
VRX1500	Takes 6 $\frac{1}{3}$ GN pans or 5 x $\frac{1}{3}$ and 1 $\frac{1}{2}$ pans not supplied	1500 x 395 x 435 mm	48kg
VRX1800	Takes 8 $\frac{1}{3}$ GN pans not supplied	1800 x 395 x 435 mm	51kg

S/S CANOPY VRX1200S/VRX1500S/VRX1800S

Product Specifications

- Interior and exterior stainless steel
- Stainless steel canopy on hinge
- Total height with lid open. 630mm
- Ambient temperature 38° C
- Digital dixell controller
- Adjustable feet



VRX1200s	Takes 4 $\frac{1}{3}$ GN pans or 3 x $\frac{1}{3}$ and 1 $\frac{1}{2}$ pans not supplied	1200 x 395 x 255 mm	24kg
VRX1500s	Takes 6 $\frac{1}{3}$ GN pans or 5 x $\frac{1}{3}$ and 1 $\frac{1}{2}$ pans not supplied	1500 x 395 x 255 mm	28kg
VRX1800s	Takes 8 $\frac{1}{3}$ GN pans not supplied	1800 x 395 x 255 mm	34kg