



|                     |                               |
|---------------------|-------------------------------|
| Technical Data:     |                               |
| Dimensions          | 200 x 600 x 850/900 mm        |
| Tank Capacity       | 8 litres                      |
| Basket Dimensions   | 158 x 285 x 135 mm            |
| Production Capacity | Up to 27 kg/h                 |
| Voltage             | 415 V                         |
| Heating Power       | 9 kW                          |
| Current             | 20 A                          |
| Temperature range   | 95° C - 190° C                |
| Net Weight          | 41 kg                         |
| Protection Index    | IPX5                          |
| Power Cable         | 2.5 m (supplied without plug) |

Product Description:

- Automatic basket lifting system (up & down) with end-of-cycle lift.
- Pump system with automatic oil filtration (metal filter + microfilter) to extend oil life.
- Electronic temperature control ( $\pm 1^{\circ}\text{C}$ ) with 6 configurable programmes.
- FrySmart Technology™ for oil-absence detection and enhanced safety.
- Operating modes: ECO (energy saving), MELT (fat melting), CLEAN (hot cleaning).
- Energy optimisation interface, smart safety key, overheating protection, removable electrical box.
- High insulation and cold-zone tank to reduce energy loss and oil degradation.
- Swiss-made stainless steel, rounded corners, swivel heating element, adjustable height (850–900 mm).

Included Accessories:

- 1 basket
- 1 container with a metal filter on top
- Additional microfilter

Optional Accessories:

- Fish grid, Fine meshed Basket and a Draining rack



Front View



Top View



Side View

