

Concrete In-Fill Type (P20-4545L to P20-9075H)

Part No.	Load Rating			Dimensions (mm)		Weight (Kg)
	Light Duty	Medium Duty	Heavy Duty	Length	Width	
	Recommended Maximum Wheel Load					
	2.5 Tonne	5 Tonne	8 Tonne			
P20-4545L	●					25
P20-4545M		●		450	450	36
P20-4545H			●			40
P20-6045L	●					32
P20-6045M		●		600	450	44
P20-6045H			●			50
P20-6060L	●					36
P20-6060M		●		600	600	51
P20-6060H			●			56
P20-7540L	●					39
P20-7540M		●		750	450	53
P20-7540H			●			61
P20-7560L	●					43
P20-7560M		●		750	600	59
P20-7560H			●			65
P20-7575L	●					44
P20-7575M		●		750	750	65
P20-7575H			●			69
P20-9045L	●					40
P20-9045M		●		900	450	54
P20-9045H			●			59
P20-9060L	●					46
P20-9060M		●		900	600	68
P20-9060H			●			75
P20-9075L	●					53
P20-9075M		●		900	750	78
P20-9075H			●			83

- Light Duty = 60mm thick; Medium Duty = 75mm thick; Heavy Duty = 75mm thick.
- Cover dimensions are nominal CLEAR OPENING and may vary according to load rating and material of manufacture.
- Standard supply covers are Concrete In-Fill Type but can be supplied as Solid Top by request.
- Non-standard cover sizes and materials can be supplied. Price and availability on application.
- Tile Edge covers available by request. Price on application.
- Wheel Load refers to single point load capacity.

- Australia wide delivery.
- Non-standard tanks made to order. Price and availability on application.
- Any sale made is subject to Viking Plastics Engineering Pty Ltd 'Terms & Conditions of Trade' document, a copy of which is available on request.
- Dimensions subject to change without notice.

- This document is intended only for the use of the individual to whom it was forwarded by Viking Plastics Engineering Pty Ltd and contains information that is confidential and privileged. If you are not the intended recipient, you must not use, read, disclose, forward, copy or store any of the information. If you have received this document in error, please dispose of it and advise Viking Plastics +61 3 9587 2297.

Concrete In-Fill Type (P20-9090L to P20-19060H)

Part No.	Load Rating			Dimensions (mm)		Weight (Kg)
	Light Duty	Medium Duty	Heavy Duty	Length	Width	
	Recommended Maximum Wheel Load					
	2.5 Tonne	5 Tonne	8 Tonne			
P20-9090L	●					57
P20-9090M		●		900	900	89
P20-9090H			●			98
P20-12545L	●					68
P20-12545M		●		1250	450	97
P20-12545H			●			106
P20-12560L	●					68
P20-12560M		●		1250	600	97
P20-12560H			●			106
P20-12575L	●					72
P20-12575M		●		1250	750	106
P20-12575H			●			116
P20-12590L	●					80
P20-12590M		●		1250	900	124
P20-12590H			●			138
P20-14060L	●					72
P20-14060M		●		1400	600	103
P20-14060H			●			113
P20-14075L	●					80
P20-14075M		●		1400	750	122
P20-14075H			●			132
P20-14090L	●					87
P20-14090M		●		1400	900	143
P20-14090H			●			159
P20-19060L	●					94
P20-19060M		●		1900	600	136
P20-19060H			●			148

- Light Duty = 60mm thick; Medium Duty = 75mm thick; Heavy Duty = 75mm thick.
- Cover dimensions are nominal CLEAR OPENING and may vary according to load rating and material of manufacture.
- Standard supply covers are Concrete In-Fill Type but can be supplied as Solid Top by request.
- Non-standard cover sizes and materials can be supplied. Price and availability on application.
- Tile Edge covers available by request. Price on application.
- Wheel Load refers to single point load capacity.

- Australia wide delivery.
- Non-standard tanks made to order. Price and availability on application.
- Any sale made is subject to Viking Plastics Engineering Pty Ltd 'Terms & Conditions of Trade' document, a copy of which is available on request.
- Dimensions subject to change without notice.

- This document is intended only for the use of the individual to whom it was forwarded by Viking Plastics Engineering Pty Ltd and contains information that is confidential and privileged. If you are not the intended recipient, you must not use, read, disclose, forward, copy or store any of the information. If you have received this document in error, please dispose of it and advise Viking Plastics +61 3 9587 2297.

Product Catalogue – Victoria September 2024

Tel: 03 9587 2297

Viking Plastics Engineering Pty Ltd | 143 Woodlands Dve, Braeside, Victoria 3195
 Fax: 03 9587 1172 | info@vikingplastics.com.au | www.vikingplastics.com.au



Concrete In-Fill Type (P20-19075L to P20-45090H)

Part No.	Load Rating			Dimensions (mm)		Weight (Kg)
	Light Duty	Medium Duty	Heavy Duty	Length	Width	
	Recommended Maximum Wheel Load					
	2.5 Tonne	5 Tonne	8 Tonne			
P20-19075L	●					103
P20-19075M		●		1900	750	160
P20-19075H			●			170
P20-19090L	●					103
P20-19090M		●		1900	900	160
P20-19090H			●			170
P20-24075L	●					131
P20-24075M		●		2400	750	205
P20-24075H			●			215
P20-24090L	●					148
P20-24090M		●		2400	900	228
P20-24090H			●			252
P20-29090L	●					172
P20-29090M		●		2900	900	270
P20-29090H			●			301
P20-40090L	●					247
P20-40090M		●		4000	900	375
P20-40090H			●			412
P20-45090L	●					277
P20-45090M		●		4500	900	428
P20-45090H			●			481

- Light Duty = 60mm thick; Medium Duty = 75mm thick; Heavy Duty = 75mm thick.
- Cover dimensions are nominal CLEAR OPENING and may vary according to load rating and material of manufacture.
- Standard supply covers are Concrete In-Fill Type but can be supplied as Solid Top by request.
- Non-standard cover sizes and materials can be supplied. Price and availability on application.
- Tile Edge covers available by request. Price on application.
- Wheel Load refers to single point load capacity.

- Australia wide delivery.
- Non-standard tanks made to order. Price and availability on application.
- Any sale made is subject to Viking Plastics Engineering Pty Ltd 'Terms & Conditions of Trade' document, a copy of which is available on request.
- Dimensions subject to change without notice.

- This document is intended only for the use of the individual to whom it was forwarded by Viking Plastics Engineering Pty Ltd and contains information that is confidential and privileged. If you are not the intended recipient, you must not use, read, disclose, forward, copy or store any of the information. If you have received this document in error, please dispose of it and advise Viking Plastics +61 3 9587 2297.