

Technical data sheet for

FAST FRI TWIN PAN ELECTRIC FRYER 450mm

FN8224EE



- 17kW high performance twin pan fryer
- 2 digital display temperature control 4 basket timers
- Easy clean stainless steel open pan with 10 year limited warranty
- 12L per pan oil capacity
- 25mm (1") drain valves
- Stainless steel exterior
- Easy service
- Fully modular
- Low back model (FNL) available

Overall Construction

- Stainless steel pan
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.5mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- Hinge out counterbalanced heating elements
- 25mm (1") drain valves
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet
- 2 baskets and stainless steel lid supplied standard

Controls

- Digital display electronic thermostats
- Thermostat range 88-195°C
- 2 programmable basket timers with countdown display and alarms per pan
- Heating and basket drop displays
- Programmable melt cycles
- Fail-safe over-temperature safety cut-outs
- Element tilt switch for heating cut-out on element lift

Cleaning and Servicing

- Open stainless steel pans with hinge out elements for easy clean
 - Easy clean basket support bar
 - 25mm (1") drain valves for effective draining
 - Easy clean stainless steel exterior
 - Access to all parts from front of unit
-

Specifications

Production rate

31kg/hr

Pan Size (per pan)

Oil capacity 12L (24lbs shortening)

Width 175mm

Length 380mm

Oil frying depth 95mm

Baskets

2 chrome plated wire baskets

140mm W x 335mm D x 145mm H

Elements (per pan)

3 x 2.83kW stainless steel heating elements

Electrical requirements

17kW, 400-415Vac, 50/60hz, 3P+N+E

L1 23.6A

L2 23.6A

L3 23.6A

Electrical connection

62mm from RH side, 365mm from rear,
and 440mm from floor

DIMENSIONS

Width 450mm

Depth 805mm

Height 915mm

Incl. splashback 1130mm

Incl. low back 1085mm

NETT WEIGHT

74kg

PACKING DATA

0.54m³, 116kg

Width 870mm

Depth 495mm

Height 1255mm

OPTIONS AT EXTRA COST

Waldorf Filtamax filtration system

Extra baskets




Side splash guards

Joining caps

Castors

Plinth mounting

FN8224EE



moffat.com.au

moffat.co.nz

Australia

moffat.com.au

Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road

Mulgrave, Victoria 3170

Telephone +613-9518 3888

Facsimile +613-9518 3833

vsales@moffat.com.au

New South Wales

Telephone +612-8833 4111

nswsales@moffat.com.au

South Australia

Telephone +613-9518 3888

vsales@moffat.com.au

Queensland

Telephone +617-3630 8600

qldsales@moffat.com.au

Western Australia

Telephone +618-9413 2400

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au

wasaes@moffat.com.au



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
AN.W8.08/19