

Induction Range Convection Oven 900mm

INLB8410ECR3 - GN 2/1 Electric Convection Oven with 4 x 3.5kW Round Induction


INLB8410ECR5 - GN 2/1 Electric Convection Oven with 4 x 5.0kW Round Induction

INLB8410ECR5F - GN 2/1 Electric Convection Oven with 2 x 5.0kW Round and 2 x 5.0kW Full Area Induction



INLB8410ECR3/R5

INLB8410ECR5F



- Heavy-duty construction
- Four Induction zones
- R3 4 x 3.5kW Round Induction zones
- R5 4 x 5.0kW Round Induction zones
- R5F 2 x 5.0kW Round / 2 x 5kW Full Area Induction zones
- Automatic pan detection
- GN 2/1 6.1kW electric convection oven
- Dual oven circulation fans
- Drop down door
- Stainless steel exterior
- Black vitreous enamel finish to front panels
- Easy clean
- Easy service
- Fully modular

OVERALL CONSTRUCTION

- Galvanized steel chassis
- Welded hob with 2.0mm 304 stainless steel top
- Splashback and hob sides 1.2mm 304 stainless steel
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet

COOKTOP

- Two 6mm thick ceramic glass 375mm x 650mm each
- Induction air cooling with front access air filter
- Fan cooled induction cooktop oven heat protection with front exhaust

OVEN

- Fully welded and vitreous enamelled oven liner
- GN 2/1 capacity with 5 position racking
- Heavy-duty easy remove heavy wire chrome rack supports
- Vitreous enamelled removable oven spill tray
- 6.0kW heating elements
- 2 fan motors
- Drop down door
- 0.9mm 304 stainless steel door outer
- 1.0mm vitreous enamelled door inner
- 38mm high density fibreglass insulated
- Supplied with two chrome wire oven racks

CONTROLS

INDUCTION COOKTOP

- Variable power controls for each induction zone
- Heating ON indicator lights with pan detection indication
- Error mode indicator

OVEN

- 50-320°C thermostatic control
- Indicator lights for power and heating
- Oven fans and heating automatic off when door open

CLEANING AND SERVICING

- All models with easy clean stainless steel external finish
- Fully sealed cooking surface
- Removable for cleaning cooling air filter
- Removable for cleaning exhaust screen
- Removable oven racking and spill tray
- Easy clean vitreous enamel oven and door inner
- Access to all service parts from front of unit

Induction Zone Options

- R3 - 4 x 3.5kW Round Induction
- R5 - 4 x 5kW Round Induction
- R5F - 2 x 5kW Round Induction / 2 x 5.0kW Full Area Induction


Series Options

- INLB - Low back models
- INB - 215mm splashback option


Induction Range Convection Oven 900mm

INLB8410ECR3 - 2/1GN Electric Convection Oven with 4 x 3.5kW Round Induction
 INLB8410ECR5 - 2/1GN Electric Convection Oven with 4 x 5.0kW Round Induction
 INLB8410ECR5F - 2/1GN Electric Convection Oven with 2 x 5.0kW Round and 2 x 5.0kW Full Area Induction


INLB8410EC



INLB8410ECR3,
 INLB8410ECR5



INLB8410ECR5F



SPECIFICATIONS

Cooktop

INLB8410ECR3

4 x 3.5kW Ø 270mm Round Induction zones

INLB8410ECR

4 x 5.0kW Ø 270mm Round Induction zones

INLB8410EC

2 x 5.0kW Ø 270mm Round Induction zones (LH)

2 x 5.0kW Full Area Induction zones

Oven

2 x 2kW oven fan elements

1 x 2kW oven bottom element

2 x oven circulation fan motors

Oven dimensions

Width 665mm

Depth 560mm

Height 350mm

Rack size 655mm x 530mm

Rack positions 5

Electrical requirements

INLB8410ECR3

20.1kW, 400-415V, 50/60Hz, 3P+N+E

28.5A / phase

INLB8410ECR5

26.1kW, 400-415V, 50/60Hz, 3P+N+E

36.3A / phase

INLB8410ECF

26.1kW, 400-415V, 50/60Hz, 3P+N+E

36.3A / phase

Electrical connection

130mm from RH side, 32mm from rear, and 318mm from floor.

Dimensions

Width 900mm

Depth 805mm

Height 915mm

Incl. splashback 1130mm

Incl. low back 970mm

Nett weight

168.5kg

Packing data

1.03m³, 235kg

Width 945mm

Depth 865mm

Height 1255mm

OPTIONS AT EXTRA COST

Rear rollers (included standard)

Castors

Plinth mounting



moffat.com.au
 moffat.co.nz

Australia

moffat.com.au

Moffat Pty Limited

Victoria/Tasmania
 740 Springvale Road
 Mulgrave, Victoria 3170
 Telephone +613-9518 3888
 Facsimile +613-9518 3833
 vsales@moffat.com.au

New South Wales
 Telephone +612-8833 4111
 nswsales@moffat.com.au

South Australia
 Telephone +613-9518 3888
 vsales@moffat.com.au

Queensland
 Telephone +617-3630 8600
 qldsals@moffat.com.au

Western Australia
 Telephone 618-9413 2400
 wasales@moffat.com.au

New Zealand

moffat.co.nz

Moffat Limited

Rolleston
 45 Illinois Drive
 Izone Business Hub
 Rolleston 7675
 Telephone +64 3-983 6600
 Facsimile +64 3-983 6660
 sales@moffat.co.nz

Auckland

Telephone +64 9-574 3150
 sales@moffat.co.nz



ISO9001
 Quality
 Management
 Standard

Designed and manufactured by



ISO9001

All Waldorf Bold products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
 AN.WBD.S.01.23

an Ali Group Company



The Spirit of Excellence