

HYDROTAP G5 BA CUBE PLUS CHROME



BOILING



AMBIENT

FILTERED

Order Code H5C785Z00AU

Zip HydroTap Design Range Boiling, Ambient, Filtered water tap features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.



Manufacturing Code H5C785Z00AU

Capacity Residential

Tap Zip HydroTap Design Range CUBE Plus Tap (Chrome)

Water Pressure Min 170kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.35kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D313mm x H333mm

Product Approvals WaterMark, RCM

Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a Zip Certified service technician, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail

BKL2 HydroTap G5 v1.04 11.23 B, BA

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

200
333
50 Command Centre width 50

Air outlet louvre (if required)
Cut-out in doorwall, towards the top of the cabinet

285 50

Air inlet cut-out (required)
Cut-out in cabinet floor

max. 43 326

HydroTap Tap options

HydroTap Arc Plus Tap

30 162 237 134 204 87 45 54

HydroTap Cube Plus Tap

30 162 237 134 204 87 45 54

Standalone Font with Arc Plus Tap

162 237 174 204 87 45 54

Cutting detail

174
3-off, \varnothing 10 holes @ 155mm PCD, equispaced
 \varnothing 140 hole for bowl
 \varnothing 176 outline of Font
 \varnothing 35 hole for tap

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

\varnothing 35mm hole for HydroTap Tap

4mm buffer pad air space

200 min.
333
50 min. 280 50 min.
313

HydroTap G5
BA Home, BA60
shown with HydroTap Arc Plus

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.